

## SATU-O

~40° + 20° oval beam optimized for CREE XT-E



### TECHNICAL SPECIFICATIONS:

Dimensions	Ø 21.8 mm
Height	8.9 mm
Fastening	glue, pin
ROHS compliant	yes 


### MATERIAL SPECIFICATIONS:

LEDiL®

Component	Type	Material	Colour	Finish
SATU-O	Multi-lens	PMMA	clear	

### ORDERING INFORMATION:


Component	Qty in box	MOQ	MPQ	Box weight (kg)
C13297_SATU-O	2880	120	120	7.7
» Box size: 480 x 280 x 300 mm				



## PHOTOMETRIC DATA (MEASURED):

### CREE

LED XB-D  
FWHM 42.0 + 22.0°  
Efficiency 77 %  
Peak intensity 2 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




### CREE

LED XP-E  
FWHM 41.0 + 17.0°  
Efficiency 83 %  
Peak intensity 2.9 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




### CREE

LED XP-E2  
FWHM 40.0 + 17.0°  
Efficiency 85 %  
Peak intensity 3 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



### CREE


LED XP-G  
FWHM 39.0 + 23.0°  
Efficiency 79 %  
Peak intensity 2.2 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



## PHOTOMETRIC DATA (MEASURED):



### CREE®

LED XP-G2  
FWHM 39.0 + 24.0°  
Efficiency 84 %  
Peak intensity 2.2 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





### LG Innotek

LED H35B0 (LEMWA32)  
FWHM 39.0 + 24.0°  
Efficiency 84 %  
Peak intensity 2.2 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:





### LG Innotek

LED H35C0 (LEMWA33)  
FWHM 39.0 + 25.0°  
Efficiency 82 %  
Peak intensity 2 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



### LUMILEDS



LED LUXEON T  
FWHM 40.0 + 24.0°  
Efficiency 84 %  
Peak intensity 2 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



## PHOTOMETRIC DATA (MEASURED):



### LUMILEDS

LED LUXEON TX  
FWHM 40.0 + 25.0°  
Efficiency 79 %  
Peak intensity 1.9 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




### NICHIA

LED NF2x757A  
FWHM 43.0 + 26.0°  
Efficiency 81 %  
Peak intensity 1.5 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



### OSRAM

Opto Semiconductors  
LED OSLON Square EC  
FWHM 41.0 + 23.0°  
Efficiency 82 %  
Peak intensity 2 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



### OSRAM



Opto Semiconductors  
LED OSLON SSL 80  
FWHM 41.0 + 18.0°  
Efficiency 79 %  
Peak intensity 2.5 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



## PHOTOMETRIC DATA (MEASURED):

**SAMSUNG**


LED LH351Z  
FWHM 40.0 + 23.0°  
Efficiency 84 %  
Peak intensity 2.3 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



### PHOTOMETRIC DATA (SIMULATED):


#### CREE®

LED XT-E  
FWHM 20.0 + 40.0°  
Efficiency %  
LEDs/each optic 1  
Light colour White  
Required components:




#### LUMILEDS

LED LUXEON H50-2  
FWHM 22.0 + 42.0°  
Efficiency 85 %  
Peak intensity 2 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




#### NICHIA

LED NVSxx19B/NVSxx19C  
FWHM 43.0 + 24.0°  
Efficiency 82 %  
Peak intensity 2 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



#### OSRAM


Opto Semiconductors  
LED Synios P2720 1/2 mm  
FWHM 25.0 + 12.0°  
Efficiency 91 %  
Peak intensity 3.5 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



## PHOTOMETRIC DATA (SIMULATED):

SEOUL  
SEOUL SEMICONDUCTOR

LED Z8Y22P  
FWHM 43.0 + 26.0°  
Efficiency 80 %  
Peak intensity 1.7 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



## GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

## MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

## PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy  
Joensuunkatu 13  
FI-24240 SALO  
Finland

LEDiL Inc.  
228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

**Local sales and technical support**  
[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

**Shipping locations**  
Salo, Finland  
Hong Kong, China

**Distribution Partners**  
[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Ledil](#):

[C13297\\_SATU-O](#)