

I	PART NUMBER	SML-LX15IIC-RP-TR REV.	E
Ī	DATE	E.C.N. NUMBER AND REVISION COMMENTS	REV.
	03.14.03	E.C.N. #10967.	Α
ſ	07.03.03	E.C.N. #11010.	В
ſ	11.30.05	E.C.N. #11148.	С
Γ	11.28.06	E.C.N. #11361.	D
Γ	05.22.08	E.C.N. #11501.	Ε

ELECTRO-OPTICAL CHA	RACTERISTI	CS T _A =25°C	$I_f = 20 \text{mA}$		
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		635		nm	
FORWARD VOLTAGE		2.0	2.5	V _f	
REVERSE VOLTAGE	5.0			V_r	I _r =100uA
AXIAL INTENSITY		10		mcd	I _f =20mA
VIEWING ANGLE		140		2x theta	
EMITTED COLOR:	RED				
EPOXY LENS FINISH:	WATER	CLEAR LENS			

LIMITS OF SAFE OPERATION AT 25°C	:	
PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	160	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	-1.2	m W/ *C
OPERATING TEMP.	-40 TO +85	.C
STORAGE TEMP.	-40 TO +85	.c


* t<10uS

CAUTION: MOISTURE SENSITIVE DEVICE PER JEDEC LEVEL 3 STANDARDS

NOTES:


1. THE POLARITY MARK IS ORIENTED TOWARDS THE TAPE SPROCKET HOLE.

C LEAD FREE REFLOW PROFILE



TOTAL TIME ABOVE 220°C IS 60 SECONDS MAX.

	TAPE SPEC DETAIL
	4.00 [0.157]
	1.75 [0.069]
8.00 [0.315]	3.50 [0.138]
-	4.00 [0.157]
	TAPE FEED DIRECTION ————



*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= $\frac{+DECIMAL}{-DECIMAL}$ PRECISION UNCONTROLLED DOCUMENT



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.6538 WEB: WWW.LUMEX.COM

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROFICE SMAN IN WHOLE OR IN PART FROM DISCLOSUME AND DISSEMINATION TO ALL THIRD PARTIES.

SOT-23 REPLACEMENT, SM LED, 635nm RED LED, REVERSE POLARITY, WATER CLEAR LENS, TAPE AND REEL.

DATE: 11.28.06		DRAWN BY: JC	1
PAGE:	1 OF 1	CHKD BY: -	
SCALE:	N/A	APRVD BY: -	
UNIT: mm [INCH]		2	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SML-LX15IIC-RP-TR