



THIS DRAWING IS UNPUBLISHED.  
RELEASED FOR PUBLICATION  
ALL RIGHTS RESERVED.

© COPYRIGHT - By -

NOTES:

- ELECTRICAL DATA: CONTACT RESISTANCE: 10 mOhm MAX  
INSULATION RESISTANCE: 100 MOhm MIN at 500VDC  
CURRENT RATING: 5 AMPS (FOR 3, 4 AND 5 POSITIONS) AND 2 AMPS (FOR 8 POSITIONS)  
BREAKDOWN VOLTAGE: 500 VAC MIN PER MINUTE
- ENVIRONMENTAL: OPERATING TEMPERATURE: -25°C TO +90°C  
SEALING REQUIREMENTS: IP67
- PACKAGING: 107-3334
- SEAL FOR CABLE OD: Ø4.5mm - Ø6.5mm
- FOR TECHNICAL DATA REFER TO YOUR LOCAL TE CONNECTIVITY SALES OFFICE.
- ALL DIMENSIONS ARE FOR NOMINAL REFERENCE ONLY UNLESS OTHERWISE STATED.

REVISIONS			
P	LTR	DESCRIPTION	DATE DWN APVD
A2 KEYING POSITION CORRECTED IN ZONE A4 & A3 27FEB2017 TJ NG			



THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN A. Morey CHK F. Wheeler-King APVD F. Wheeler-King	14MAR06 12APR06 12APR06	NAME M12 PLASTIC FIELD SERVICEABLE CONNECTOR, MALE PIN, SOLDER TYPE
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED	—	—	
0 PLC 1 PLC 2 PLC 3 PLC 4 PLC	± ± ± ± ±	—	—	APPLICATION SPEC —
MATERIAL REFER BOM TABLE	FINISH REFER BOM TABLE	ANGLES —	WEIGHT 0	SIZE CAGE CODE DRAWING NO A2 00779 C-1838277 RESTRICTED TO —
				CUSTOMER DRAWING SCALE NTS SHEET 1 OF 1 REV A2

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1838277-2](#)