

## Insert label - EMT (24X4)R - 0816265

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Insert label, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK X, THERMOMARK S1.1, Mounting type: Insert, Cable diameter: ≤12 mm, Lettering field: 24 x 4 mm

The figure shows the EMT (40x17)R version

### Product Features

- PABL ... sheets are available for labeling with a laser printer
- Can be printed with THERMOMARK... for material off the roll
- Thanks to their special shape, EMT ... insert labels remain securely inside the collar once inserted
- EMT ... insert labels for labeling various marking collars



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Weight per Piece (excluding packing) | 523.0 g  |
| Custom tariff number                 | 39269092 |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|            |       |
|------------|-------|
| Length (b) | 24 mm |
| Width (a)  | 4 mm  |

#### Ambient conditions

|                                 |                                |
|---------------------------------|--------------------------------|
| Ambient temperature (operation) | -40 °C ... 120 °C              |
| Recommended storage conditions  | 23 °C / 50 % relative humidity |

#### General

|            |                                |
|------------|--------------------------------|
| Color      | white                          |
| Components | free from silicone and halogen |

## Insert label - EMT (24X4)R - 0816265

### Technical data

#### General

|                                                                     |                               |
|---------------------------------------------------------------------|-------------------------------|
| Material                                                            | Polyester                     |
| Wipe resistance                                                     | DIN EN 61010-1 (VDE 0411-1)   |
| Number of individual labels                                         | 5000                          |
| Number of individual labels per row                                 | 4                             |
| RoHS compliant                                                      | Yes                           |
| Printability                                                        | Thermal transfer              |
| Device                                                              | 5146477 THERMOMARK ROLL       |
|                                                                     | 5145274 THERMOMARK X1.1       |
|                                                                     | 5146231 THERMOMARK X1.2       |
|                                                                     | 5145313 THERMOMARK S1         |
|                                                                     | 5146257 THERMOMARK S1.1       |
| Ink ribbon                                                          | 5145384 THERMOMARK-RIBBON 110 |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02          |
| Result                                                              | Test passed                   |
| Test specification weathering-resistance                            | Following ISO 4892-2:2013-03  |
| Test duration                                                       | 96 h                          |
| Wipe resistance test result                                         | Test passed                   |
| Salt spray test specification                                       | DIN EN ISO 9227:2012-09       |
| Test duration                                                       | 96 h                          |
| Salt spray testing result                                           | Test passed                   |
| Alternating condensation climate with SO2 test specification        | DIN 50018:2013-05             |
| Climate level                                                       | AHT 1.0 S                     |
| Cycles                                                              | 2                             |
| Condensation test result                                            | Test passed                   |
| Foil strength                                                       | 175 µm                        |
| Marking mounting type                                               | Insert                        |

#### Standards and Regulations

|                 |                             |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 24190219 |
| eCl@ss 4.1 | 24190219 |
| eCl@ss 5.0 | 27141137 |
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27141137 |

## Insert label - EMT (24X4)R - 0816265

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 7.0 | 27141137 |
| eCl@ss 8.0 | 27149129 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC001530 |
| ETIM 5.0 | EC001288 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

### Accessories

#### Accessories

##### Ink ribbon

Ink ribbon - THERMOMARK-RIBBON 110 - 5145384



Ink ribbon, Length: 300000 mm, Width: 110 mm, Color: black

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact:

0816265