

Specification Sheet

Part Number: TSR2FW-6A



One Piece Surface Raceway, 1-1/4", 6.0 ft Long, PVC, Office White, 120ft/Carton

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 250-02601                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Type                | TSR2-6A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Color               | Office White (OEWH)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Features & Benefits | <ul style="list-style-type: none"><li>• Tamper resistant covers with hidden latch provide security while allowing quick entry for cable maintenance.</li><li>• PVC construction is lightweight, durable and more affordable than metallic raceway systems.</li><li>• Flexible hinge is designed to reduce stress cracking and discoloration from repeated opening and closing.</li><li>• Foam tape backing with rubber based adhesive conforms to any flat surface to assist with temporary positioning and mounting.</li><li>• Systems and fittings are available in white, office white and ivory to coordinate with a variety of décor.</li><li>• Fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.</li></ul> |
| Quantity Per        | carton                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Description</b> | HellermannTyton surface raceway systems are the ideal solution for routing communication and power cables. No need to break into existing walls - raceway systems are designed to route cable along wall surfaces. Made of a PVC material, components are durable and affordable; and the one-piece construction and adhesive tape backing make positioning and mounting easy. HellermannTyton offers a low voltage TSR system and a power rated TSRP system that are available in three different diameters to accommodate different cable and wire bundle and conduit sizes. Both systems include a complete line of fittings and junction boxes that allow for clean and professional installations. |
| <b>Short Description</b>   | One Piece Surface Raceway, 1-1/4", 6.0 ft Long, PVC, Office White, 120ft/Carton                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Global Part Name</b>    | TSR2-6A-PVC-WH                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Length L (Imperial)</b> | 6.0                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Length L (Metric)</b>   | 1.83                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Width W (Imperial)</b>  | 1.25                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Width W (Metric)</b>    | 31.75                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Height H (Imperial)</b> | .75                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Height H (Metric)</b>   | 19.05                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Material</b>            | Polyvinylchloride (PVC)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Material Shortcut</b>   | PVC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

|                                       |                |
|---------------------------------------|----------------|
| <b>Flammability</b>                   | UL 94 V0       |
| <b>Halogen free</b>                   | No             |
| <b>Operating Temperature (Metric)</b> | +122°F (+50°C) |
| <b>Reach Complaint(Article 33)</b>    | No             |
| <b>ROHS Complaint</b>                 | Yes            |
| <b>Package Quantity(Imperial)</b>     | 120            |
| <b>Package Quantity (Metric)</b>      | 36.58          |
| <b>Customs Number</b>                 | 3925900000     |