


D



RECOMMENDED HOLE LAYOUT

- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
- TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK.  
POST: COPPER ALLOY
- FINISH: 0.00254–0.00508 [.000100–.000200] MATTE TIN-LEAD  
OVER 0.00127 [.000050] NICKEL ENTIRE POST.
- FINISH: 0.00254–0.00508 [.000100–.000200] MATTE TIN  
OVER 0.00127 [.000050] NICKEL ENTIRE POST.

PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER
△	101.19	99.06	39	40	9-146460-0
△	98.65	96.52			
△	3.984	3.900	38	39	8-146460-9
△	96.11	93.98			
△	3.884	3.800			
△	96.11	93.98	37	38	8-146460-8
△	3.784	3.700			
△	93.57	91.44	36	37	8-146460-7
△	3.684	3.600			
△	91.03	88.90	35	36	8-146460-6
△	3.584	3.500			
△	88.49	86.36	34	35	8-146460-5
△	3.484	3.400			
△	85.95	83.82	33	34	8-146460-4
△	3.384	3.300			
△	83.41	81.28	32	33	8-146460-3
△	3.284	3.200			
△	80.87	78.74	31	32	8-146460-2
△	3.184	3.100			
△	78.33	76.20	30	31	8-146460-1
△	3.084	3.000			
△	75.79	73.66	29	30	8-146460-0
△	2.984	2.900			
△	73.25	71.12	28	29	7-146460-9
△	2.884	2.800			
△	70.71	68.58	27	28	7-146460-8
△	2.784	2.700			
△	68.17	66.04	26	27	7-146460-7
△	2.684	2.600			
△	65.63	63.50	25	26	7-146460-6
△	2.584	2.500			
△	63.09	60.96	24	25	7-146460-5
△	2.484	2.400			
△	60.55	58.42	23	24	7-146460-4
△	2.384	2.300			
△	58.01	55.88	22	23	7-146460-3
△	2.284	2.200			
△	55.47	53.34	21	22	7-146460-2
△	2.184	2.100			
△	52.93	50.80	20	21	7-146460-1
△	2.084	2.000			
△	50.39	48.26	19	20	7-146460-0
△	1.984	1.900			
△	47.85	45.72	18	19	6-146460-9
△	1.884	1.800			
△	45.31	43.18	17	18	6-146460-8
△	1.784	1.700			
△	42.77	40.64	16	17	6-146460-7
△	1.684	1.600			
△	40.23	38.10	15	16	6-146460-6
△	1.584	1.500			
△	37.69	35.56	14	15	6-146460-5
△	1.484	1.400			
△	35.15	33.02	13	14	6-146460-4
△	1.384	1.300			
△	32.61	30.48	12	13	6-146460-3
△	1.284	1.200			
△	30.07	27.94	11	12	6-146460-2
△	1.184	1.100			
△	27.53	25.40	10	11	6-146460-1
△	1.084	1.000			
△	24.99	22.86	9	10	6-146460-0
△	.984	.900			
△	22.45	20.32	8	9	5-146460-9
△	.884	.800			
△	19.91	17.78	7	8	5-146460-8
△	.784	.700			
△	17.37	15.24	6	7	5-146460-7
△	.684	.600			
△	14.83	12.70	5	6	5-146460-6
△	.584	.500			
△	12.29	10.16	4	5	5-146460-5
△	.484	.400			
△	9.75	7.62	3	4	5-146460-4
△	.384	.300			
△	7.21	5.08	2	3	5-146460-3
△	.284	.200			
△	4.67	2.54	1	2	5-146460-2
△	.184	.100			
△	2.13	—	—	1	5-146460-1
△	.084	—	—	—	146460-1

PLATING G F E NO. OF POSITIONS PART NUMBER

PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER
△	101.19	99.06	39	40	4-146460-0
△	98.65	96.52			
△	3.984	3.800	38	39	3-146460-9
△	96.11	93.98			
△	3.884	3.700	37	38	3-146460-8
△	93.57	91.44			
△	3.684	3.600	36	37	3-146460-7
△	91.03	88.90			
△	3.584	3.500	35	36	3-146460-6
△	88.49	86.36			
△	3.484	3.400	34	35	3-146460-5
△	85.95	83.82			
△	3.384	3.300	33	34	3-146460-4
△	83.41	81.28			
△	3.284	3.200	32	33	3-146460-3
△	80.87	78.74			
△	3.184	3.100	31	32	3-146460-2
△	78.33	76.20			
△	3.084	3.000	30	31	3-146460-1
△	75.79	73.66			
△	2.984	2.900	29	30	3-146460-0
△	73.25	71.12			
△	2.884	2.800	28	29	2-146460-9
△	70.71	68.58			
△	2.784	2.700	27	28	2-146460-8
△	68.17	66.04			
△	2.684	2.600	26	27	2-146460-7
△	65.63	63.50			
△	2.584	2.500	25	26	2-146460-6
△	63.09	60.96			
△	2.484	2.400	24	25	2-146460-5
△	60.55	58.42			
△	2.384	2.300	23	24	2-146460-4
△	58.01	55.88			
△	2.284	2.200	22	23	2-146460-3
△	55.47	53.34			
△	2.184	2.100	21	22	2-146460-2
△	52.93	50.80			
△	2.084	2.000	20	21	2-146460-1
△	50.39	48.26			
△	1.984	1.900	19	20	2-146460-0
△	47.85	45.72			
△	1.884	1.800	18	19	1-146460-9
△	45.31	43.18</td			

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[6-146460-4](#)