

## Fork-type cable lug - C-FC 2,5/M5 - 3240145

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fork-type cable lug, non-insulated, 1.1 - 2.5 mm<sup>2</sup>, M5

### Product Features

- The fork-type cable lugs without plastic sleeve feature a hard-soldered neck. In conjunction with the CRIMPFOX-RC ... and CRIMPFOX-RCI ... pliers they can be used to achieve maximum conductor pull-out forces
- The insulated versions are halogen-free and feature "EASY ENTRY" technology



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 100 pc   |
| Weight per Piece (excluding packing) | 0.1 g    |
| Custom tariff number                 | 85369010 |
| Country of origin                    | China    |

### Technical data

#### Dimensions

|                                              |        |
|----------------------------------------------|--------|
| Length (b)                                   | 16 mm  |
| Width (a)                                    | 8 mm   |
| Maximum stripping length                     | 8 mm   |
| Length of insulation sleeve (c)              | 4.8 mm |
| Inner dimension of the insulating collar (d) | 2.5 mm |
| Inner diameter (f)                           | 5.3 mm |
| Material thickness (g)                       | 0.8 mm |

#### Ambient conditions

|                                 |        |
|---------------------------------|--------|
| Ambient temperature (operation) | 110 °C |
|---------------------------------|--------|

#### General

## Fork-type cable lug - C-FC 2,5/M5 - 3240145

### Technical data

#### General

|                  |              |
|------------------|--------------|
| Color            | silver       |
| Stripping length | 8 mm         |
| Components       | Halogen-free |
| Material         | Copper       |
| Coating          | Tin-plated   |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060701 |
| eCl@ss 4.1 | 27060701 |
| eCl@ss 5.0 | 27400201 |
| eCl@ss 5.1 | 27400201 |
| eCl@ss 6.0 | 27400201 |
| eCl@ss 7.0 | 27400201 |
| eCl@ss 8.0 | 27400204 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000005 |
| ETIM 3.0 | EC000005 |
| ETIM 4.0 | EC001052 |
| ETIM 5.0 | EC001052 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211923 |
| UNSPSC 7.0901 | 27121703 |
| UNSPSC 11     | 27121703 |
| UNSPSC 12.01  | 27121703 |
| UNSPSC 13.2   | 27121703 |

### Approvals

#### Approvals

---

Approvals

EAC

---

## Fork-type cable lug - C-FC 2,5/M5 - 3240145

### Approvals

Ex Approvals

---

Approvals submitted


---

### Approval details

|     |
|-----|
| EAC |
|-----|

### Drawings

Dimensional drawing



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[3240145](#)