

## High Pulse Load Carbon Film MELF Resistors



### FEATURES

- Approved to the safety requirements of IEC 60065, 14.2.a (= VDE 0860, 14.1.a) VDE-REG.-Nr. B583
- AEC-Q200 qualified
- Special carbon film technology
- Up to 3 kW single pulse capability
- ESD capability: 16 kV, human body model
- Sulfur resistance verified according to ASTM B 809
- Surge voltage capability up to 10 kV 1.2/50  $\mu$ s pulse
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

**HALOGEN**  
**FREE**
**GREEN**  
(5-2008)

CMB 0207 carbon film MELF resistors with advanced pulse load capability are the perfect choice for the protection of circuitry with signal and mains input lines from surge pulses. The resistors are also suitable for circuits exposed to high levels of electromagnetic interference or electro-static discharge. The applications are in all fields of automotive, telecommunication, industrial and medical equipment.

### APPLICATIONS

- Automotive
- Telecommunication
- Industrial
- Medical equipment

| TECHNICAL SPECIFICATIONS                                              |                                      |
|-----------------------------------------------------------------------|--------------------------------------|
| DESCRIPTION                                                           | CMB 0207                             |
| DIN size                                                              | 0207                                 |
| Metric size code                                                      | RC6123M                              |
| Resistance range                                                      | 2.2 $\Omega$ to 1.5 M $\Omega$       |
| Resistance tolerance                                                  | $\pm 5\%$ ; $\pm 2\%$ ; $\pm 1\%$    |
| Temperature coefficient                                               | see TCR graph                        |
| Rated dissipation, $P_{70}$ <sup>(1)</sup>                            | 1.0 W                                |
| Operating voltage, $U_{max}$ AC <sub>RMS</sub> /DC                    | 500 V                                |
| Permissible film temperature, $\vartheta_{F max}$ <sup>(1)</sup>      | 155 $^{\circ}$ C                     |
| Operating temperature range <sup>(1)</sup>                            | -55 $^{\circ}$ C to 155 $^{\circ}$ C |
| Permissible voltage against ambient (insulation):<br>1 min; $U_{ins}$ | 750 V                                |
| Failure rate: FIT <sub>observed</sub>                                 | $\leq 0.1 \times 10^{-9}/h$          |

#### Note

<sup>(1)</sup> Please refer to APPLICATION INFORMATION below.

### APPLICATION INFORMATION

The power dissipation on the resistor generates a temperature rise against the local ambient, depending on the heat flow support of the printed-circuit board (thermal resistance). The rated dissipation applies only if the permitted film temperature is not exceeded. Furthermore, a high level of ambient temperature or of power dissipation may raise the temperature of the solder joint, hence special solder alloys or board materials may be required to maintain the reliability of the assembly.

These resistors do not feature a limited lifetime when operated within the permissible limits. However, resistance value drift increasing over operating time may result in exceeding a limit acceptable to the specific application, thereby establishing a functional lifetime. At the maximum permissible film temperature of 155  $^{\circ}$ C the useful lifetime is specified for 8000 h. The designer may estimate the performance of the particular resistor application or set certain load and temperature limits in order to maintain a desired stability.

**MAXIMUM RESISTANCE CHANGE AT RATED DISSIPATION**

| OPERATION MODE                                                                    |          | STANDARD                      | POWER                         |
|-----------------------------------------------------------------------------------|----------|-------------------------------|-------------------------------|
| Rated dissipation, $P_{70}$                                                       | CMB 0207 | 0.4 W                         | 1.0 W <sup>(1)</sup>          |
| Operating temperature range                                                       |          | -55 °C to 125 °C              | -55 °C to 155 °C              |
| Permissible film temperature, $\theta_F$ max.                                     |          | 125 °C                        | 155 °C                        |
| Max. resistance change at $P_{70}$<br>for resistance range, $ \Delta R/R $ after: | CMB 0207 | 2.2 $\Omega$ to 10 k $\Omega$ | 2.2 $\Omega$ to 10 k $\Omega$ |
|                                                                                   | 1000 h   | $\leq 0.5 \%$                 | $\leq 1 \%$                   |
|                                                                                   | 8000 h   | $\leq 1 \%$                   | $\leq 2 \%$                   |

**Note**

<sup>(1)</sup> Specified power rating requires dedicated heat sink pads.

**TEMPERATURE COEFFICIENT AND RESISTANCE RANGE**

| TYPE / SIZE | TCR           | TOLERANCE  | RESISTANCE                    | E-SERIES |
|-------------|---------------|------------|-------------------------------|----------|
| CMB 0207    | see TCR graph | $\pm 5 \%$ | 2.2 $\Omega$ to 15 $\Omega$   | E24      |
|             |               | $\pm 2 \%$ | 16 $\Omega$ to 1.5 M $\Omega$ | E24      |
|             |               | $\pm 1 \%$ | 16 $\Omega$ to 1 M $\Omega$   | E24; E96 |

**PACKAGING**

| TYPE / SIZE | CODE | QUANTITY | PACKAGING STYLE                                                | WIDTH | PITCH | PACKAGING DIMENSIONS       |
|-------------|------|----------|----------------------------------------------------------------|-------|-------|----------------------------|
| CMB 0207    | B2   | 2000     | Antistatic blister tape<br>acc. IEC 60286-3 Type 2a<br>on reel | 12 mm | 4 mm  | $\varnothing$ 180 mm / 7"  |
|             | B7   | 7000     |                                                                |       |       | $\varnothing$ 330 mm / 13" |

**PART NUMBER AND PRODUCT DESCRIPTION**

Part Number: CMB02070X4701GB200

|             |   |             |   |   |   |                   |   |   |                                                                                                                                                                                                                                    |   |   |   |                                     |   |           |   |   |
|-------------|---|-------------|---|---|---|-------------------|---|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|---|---|-------------------------------------|---|-----------|---|---|
| C           | M | B           | 0 | 2 | 0 | 7                 | 0 | X | 4                                                                                                                                                                                                                                  | 7 | 0 | 1 | G                                   | B | 2         | 0 | 0 |
| TYPE / SIZE |   | VERSION     |   |   |   | TCR               |   |   | VALUE                                                                                                                                                                                                                              |   |   |   | TOLERANCE                           |   | PACKAGING |   |   |
| CMB0207     |   | 0 = neutral |   |   |   | X = no indication |   |   | 3 digit value<br>1 digit multiplier<br><b>Multiplier</b><br>8 = *10 <sup>-2</sup><br>9 = *10 <sup>-1</sup><br>0 = *10 <sup>0</sup><br>1 = *10 <sup>1</sup><br>2 = *10 <sup>2</sup><br>3 = *10 <sup>3</sup><br>4 = *10 <sup>4</sup> |   |   |   | J = ± 5 %<br>G = ± 2 %<br>F = ± 1 % |   | B2<br>B7  |   |   |

Product Description: CMB 0207 2 % B2 4K7

|      |      |                                        |           |                                             |
|------|------|----------------------------------------|-----------|---------------------------------------------|
| CMB  | 0207 | 2 %                                    | B2        | 4K7                                         |
| TYPE | SIZE | TOLERANCE                              | PACKAGING | RESISTANCE VALUE                            |
| CMB  | 0207 | $\pm 5 \%$<br>$\pm 2 \%$<br>$\pm 1 \%$ | B2<br>B7  | 100R = 100 $\Omega$<br>4K7 = 4.7 k $\Omega$ |

**Note**

- Products can be ordered using either the PART NUMBER or the PRODUCT DESCRIPTION.



## DESCRIPTION

Production of the CMB 0207 specialty MELF resistor is strictly controlled and follows an extensive set of instructions established for reproducibility. A homogeneous and dense carbon film is deposited on a high grade ceramic body ( $\text{Al}_2\text{O}_3$ ). Nickel plated steel termination caps are firmly pressed on the coated rods. Products with a resistance of 15  $\Omega$  or lower are made without trimming, whereas a special laser is used to achieve a target value of 16  $\Omega$  or above by smoothly cutting a helical groove in the resistive layer without damaging the ceramics. The resistor elements are covered by a protective coating designed for electrical, mechanical and climatic protection. The terminations receive a final pure matte tin on nickel plating. Four or five color code rings designate the resistance value and tolerance in accordance with **IEC 60062** <sup>(1)</sup>.

The result of the determined production is verified by an extensive testing procedure performed on 100 % of the individual resistors. Only accepted products are laid directly into the blister tape in accordance with **IEC 60286-3, Type 2a** <sup>(1)</sup>.

## ASSEMBLY

The resistors are suitable for processing on automatic SMD assembly systems. They are suitable for automatic soldering using wave, reflow or vapor phase as shown in **IEC 61760-1** <sup>(1)</sup>. Solderability is specified for 2 years after production or requalification, however, excellent solderability is proven after extended storage in excess of 10 years. The permitted storage time is 20 years.

The resistors are completely lead (Pb)-free, the pure matte tin plating provides compatibility with lead (Pb)-free soldering processes. The immunity of the plating against tin whisker growth has been proven under extensive testing.

The encapsulation is resistant to all cleaning solvents commonly used in the electronics industry, including alcohols, esters and aqueous solutions. The suitability of conformal coatings, potting compounds and their processes, if applied, shall be qualified by appropriate means to ensure the long-term stability of the whole system.

## MATERIALS

Vishay acknowledges the following systems for the regulation of hazardous substances:

- IEC 62474, Material Declaration for Products of and for the Electrotechnical Industry, with the list of declarable substances given therein <sup>(2)</sup>
- The Global Automotive Declarable Substance List (GADSL) <sup>(3)</sup>
- The REACH regulation (1907/2006/EC) and the related list of substances with very high concern (SVHC) <sup>(4)</sup> for its supply chain

The products do not contain any of the banned substances as per IEC 62474, GADSL, or the SVHC list, see [www.vishay.com/how/leadfree](http://www.vishay.com/how/leadfree).

Hence the products fully comply with the following directives:

- 2000/53/EC End-of-Life Vehicle Directive (ELV) and Annex II (ELV II)
- 2011/65/EU Restriction of the Use of Hazardous Substances Directive (RoHS) with amendment 2015/863/EU
- 2012/19/EU Waste Electrical and Electronic Equipment Directive (WEEE)

Vishay pursues the elimination of conflict minerals from its supply chain, see the Conflict Minerals Policy at [www.vishay.com/doc?49037](http://www.vishay.com/doc?49037).

## APPROVALS

Where applicable the resistors are tested in accordance with **EN 140401-803** which refers to **EN 60115-1, EN 60115-8** and the variety of environmental test procedures of the **IEC 60068** <sup>(1)</sup> series.

Vishay Beyschlag has achieved “**Approval of Manufacturer**” in accordance with **IECQ 03-1**. The release certificate for “**Technology Approval Schedule**” in accordance with **CECC 240001** based on **IECQ 03-3-1** is granted for the Vishay Beyschlag manufacturing process.



The resistors are qualified according to AEC-Q200.

## RELATED PRODUCTS


- “Professional Thin Film MELF Resistors” ([www.vishay.com/doc?28713](http://www.vishay.com/doc?28713))
- “Precision Thin Film MELF Resistors” ([www.vishay.com/doc?28714](http://www.vishay.com/doc?28714))
- “High Pulse Load Carbon Film MINI-MELF Resistors of case size 0204” ([www.vishay.com/doc?28717](http://www.vishay.com/doc?28717))

## Notes

- <sup>(1)</sup> The quoted IEC standards are also released as EN standards with the same number and identical contents.
- <sup>(2)</sup> The IEC 62474 list of declarable substances is maintained in a dedicated database, which is available at <http://std.iec.ch/iec62474>.
- <sup>(3)</sup> The Global Automotive Declarable Substance List (GADSL) is maintained by the American Chemistry Council and available at [www.gadsl.org](http://www.gadsl.org).
- <sup>(4)</sup> The SVHC list is maintained by the European Chemical Agency (ECHA) and available at <http://echa.europa.eu/candidate-list-table>.


**FUNCTIONAL PERFORMANCE**

**Derating - Standard Operation**

**Note**

(1) Specified power rating requires dedicated heat sink pads

**Derating - Power Operation**



Maximum pulse load, single pulse; applicable if  $\bar{P} \rightarrow 0$  and  $n \leq 1000$  and  $\bar{U} \leq 4$  kV; for permissible resistance change equivalent to 8000 h operation in power operation mode.

**Single Pulse**




Maximum pulse load, continuous pulses; applicable if  $\bar{P} \leq P(\vartheta_{amb})$  and  $\hat{U} \leq 4$  kV;  
for permissible resistance change equivalent to 8000 h operation in power operation mode.

### Continuous Pulse





Pulse load rating in accordance with IEC 60115-1, 4.27; 1.2  $\mu$ s/50  $\mu$ s; 5 pulses  
at 12 s intervals; for permissible resistance change  $\pm (0.5 \% R + 0.05 \Omega)$

### 1.2/50 Pulse



Pulse load rating in accordance with IEC 60115-1, 4.27; 10  $\mu$ s/700  $\mu$ s; 10 pulses  
at 1 min intervals; for permissible resistance change  $0.5 \% \pm (0.5 \% R + 0.05 \Omega)$

### 10/700 Pulse



In accordance with IEC 60195

## TESTS AND REQUIREMENTS

All tests are carried out in accordance with the following specifications:

EN 60115-1, generic specification

EN 60115-8 (successor of EN 140400), sectional specification

EN 140401-803, detail specification

IEC 60068-2-xx, test methods

The parameters stated in the Test Procedures and Requirements table are based on the required tests and permitted limits of EN 140401-803. The table presents only the most important tests, for the full test schedule refer to the documents listed above. However, some additional tests and a number of improvements against those minimum requirements have been included.

The testing also covers most of the requirements specified by EIA/ECA-703 and JIS-C-5201-1.

The tests are carried out under standard atmospheric conditions in accordance with IEC 60068-1, 4.3, whereupon the following values are applied:

Temperature: 15 °C to 35 °C

Relative humidity: 45 % to 75 %

Air pressure: 86 kPa to 106 kPa (860 mbar to 1060 mbar).

A climatic category LCT / UCT / 56 is applied, defined by the lower category temperature (LCT), the upper category temperature (UCT), and the duration of exposure in the damp heat, steady state test (56 days).


The components are mounted for testing on printed circuit boards in accordance with EN 60115-8, 2.4.2, unless otherwise specified.

| TEST PROCEDURES AND REQUIREMENTS |                                                       |                                                 |                                                                                                                                                                                 |                                                                |
|----------------------------------|-------------------------------------------------------|-------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| EN 60115-1<br>CLAUSE             | IEC 60068-2 (1)<br>TEST METHOD                        | TEST                                            | PROCEDURE                                                                                                                                                                       | REQUIREMENTS<br>PERMISSIBLE CHANGE ( $\Delta R$ )              |
|                                  |                                                       |                                                 | <b>Stability for product types:</b>                                                                                                                                             |                                                                |
|                                  |                                                       |                                                 | <b>CMB 0207</b>                                                                                                                                                                 | 2.2 $\Omega$ to 1.5 M $\Omega$                                 |
| 4.5                              | -                                                     | Resistance                                      | -                                                                                                                                                                               | $\pm 5 \% R$ ; $\pm 2 \% R$ ; $\pm 1 \% R$                     |
| 4.8                              | -                                                     | Temperature coefficient                         | At (20 / -55 / 20) °C<br>and (20 / 125 / 20) °C                                                                                                                                 | see Temperature Coefficient graph                              |
| 4.25.1                           | -                                                     | Endurance at 70 °C:<br>standard operation mode  | $U = \sqrt{P_{70} \times R} \leq U_{max.}$ ;<br>whichever is the less severe;<br>1.5 h on; 0.5 h off;<br>70 °C; 1000 h<br>70 °C; 8000 h                                         | $\pm (1 \% R + 0.05 \Omega)$<br>$\pm (2 \% R + 0.05 \Omega)$   |
|                                  | -                                                     | Endurance at 70 °C:<br>power operation mode     | $U = \sqrt{P_{70} \times R} \leq U_{max.}$ ;<br>whichever is the less severe;<br>1.5 h on; 0.5 h off;<br>70 °C; 1000 h<br>70 °C; 8000 h                                         | $\pm (2 \% R + 0.05 \Omega)$<br>$\pm (4 \% R + 0.05 \Omega)$   |
| 4.25.3                           | -                                                     | Endurance at upper category<br>temperature      | 125 °C; 1000 h<br>155 °C; 1000 h                                                                                                                                                | $\pm (2 \% R + 0.05 \Omega)$<br>$\pm (4 \% R + 0.05 \Omega)$   |
| 4.24                             | 78 (Cab)                                              | Damp heat, steady state                         | (40 $\pm$ 2) °C; 56 days; (93 $\pm$ 3) % RH                                                                                                                                     | $\pm (1 \% R + 0.1 \Omega)$                                    |
| 4.37                             | 67 (Cy)                                               | Damp heat,<br>steady state,<br>accelerated      | (85 $\pm$ 2) °C<br>(85 $\pm$ 5) % RH<br>$U = \sqrt{0.3 \times P_{70} \times R} \leq 100 \text{ V}$<br>and $U = 0.3 \times U_{max.}$ ;<br>(the smaller value is valid)<br>1000 h | $\pm (2 \% R + 0.1 \Omega)$                                    |
| 4.23                             | 2 (Ba)<br>30 (Db)<br>1 (Aa)<br>13 (M)<br>30 (Db)<br>- | Climatic sequence:                              |                                                                                                                                                                                 |                                                                |
| 4.23.2                           |                                                       | dry heat                                        | UCT; 16 h                                                                                                                                                                       |                                                                |
| 4.23.3                           |                                                       | damp heat, cyclic                               | 55 °C; 24 h; $\geq 90 \% \text{ RH}$ ; 1 cycle                                                                                                                                  |                                                                |
| 4.23.4                           |                                                       | cold                                            | LCT; 2 h                                                                                                                                                                        |                                                                |
| 4.23.5                           |                                                       | low air pressure                                | 8.5 kPa; 2 h; (25 $\pm$ 10) °C                                                                                                                                                  |                                                                |
| 4.23.6                           |                                                       | damp heat, cyclic                               | 55 °C; 24 h; $\geq 90 \% \text{ RH}$ ; 5 cycles                                                                                                                                 |                                                                |
| 4.23.7                           |                                                       | DC load                                         | $U = \sqrt{P_{70} \times R} \leq U_{max.}$ ; 1 min<br>LCT = -55 °C; UCT = 155 °C                                                                                                | $\pm (1 \% R + 0.1 \Omega)$                                    |
| -                                | 1 (Aa)                                                | Cold                                            | -55 °C; 2 h                                                                                                                                                                     | $\pm (0.5 \% R + 0.1 \Omega)$                                  |
| 4.19                             | 14 (Na)                                               | Rapid change of temperature                     | 30 min at LCT;<br>30 min at UCT;<br>LCT = -55 °C; UCT = 125 °C<br>5 cycles<br>1000 cycles                                                                                       | $\pm (0.5 \% R + 0.1 \Omega)$<br>$\pm (1.5 \% R + 0.1 \Omega)$ |
| 4.13                             | -                                                     | Short time overload;<br>standard operation mode | $U = 2.5 \times \sqrt{P_{70} \times R} \leq 2 \times U_{max.}$ ;<br>whichever is the less severe;<br>5 s                                                                        | $\pm (0.25 \% R + 0.1 \Omega)$                                 |
|                                  |                                                       | Short time overload;<br>power operation mode    | $U = 2.5 \times \sqrt{P_{70} \times R} \leq 2 \times U_{max.}$ ;<br>whichever is the less severe;<br>5 s                                                                        | $\pm (0.5 \% R + 0.1 \Omega)$                                  |
| 4.22                             | 6 (Fc)                                                | Vibration                                       | Endurance by sweeping;<br>10 Hz to 2000 Hz;<br>no resonance;<br>amplitude $\leq 1.5 \text{ mm}$ or<br>$\leq 200 \text{ m/s}^2$ ; 7.5 h                                          | $\pm (0.25 \% R + 0.1 \Omega)$                                 |

| TEST PROCEDURES AND REQUIREMENTS |                                           |                                               |                                                                                                                            |                                                                                         |
|----------------------------------|-------------------------------------------|-----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|
| EN 60115-1<br>CLAUSE             | IEC 60068-2 <sup>(1)</sup><br>TEST METHOD | TEST                                          | PROCEDURE                                                                                                                  | REQUIREMENTS<br>PERMISSIBLE CHANGE ( $\Delta R$ )                                       |
|                                  |                                           |                                               | Stability for product types:                                                                                               |                                                                                         |
|                                  |                                           |                                               | <b>CMB 0207</b>                                                                                                            | 2.2 $\Omega$ to 1.5 M $\Omega$                                                          |
| 4.40                             | -                                         | Electrostatic discharge<br>(human body model) | IEC 61340-3-1 <sup>(1)</sup> ;<br>3 pos. + 3 neg.<br>(equivalent to MIL-STD-883,<br>method 3015)<br>CMB 0207: 16 kV        | $\pm (0.5 \% R + 0.05 \Omega)$                                                          |
| 4.17                             | 58 (Td)                                   | Solderability                                 | Solder bath method;<br>SnPb40;<br>non-activated flux;<br>(215 $\pm$ 3) $^{\circ}\text{C}$ ; (3 $\pm$ 0.3) s                | Good tinning ( $\geq 95 \%$ covered);<br>no visible damage                              |
|                                  |                                           |                                               | Solder bath method;<br>SnAg3Cu0.5 or<br>SnAg3.5; non-activated flux;<br>(235 $\pm$ 3) $^{\circ}\text{C}$ ; (2 $\pm$ 0.2) s | Good tinning ( $\geq 95 \%$ covered);<br>no visible damage                              |
| 4.18                             | 58 (Td)                                   | Resistance to soldering heat                  | Solder bath method;<br>(260 $\pm$ 5) $^{\circ}\text{C}$ ; (10 $\pm$ 1) s                                                   | $\pm (0.5 \% R + 0.1 \Omega)$                                                           |
|                                  |                                           |                                               | Reflow method 2<br>(IR / forced gas convection);<br>(260 $\pm$ 5) $^{\circ}\text{C}$ ; (10 $\pm$ 1) s                      | $\pm (0.25 \% R + 0.1 \Omega)$                                                          |
| 4.29                             | 45 (XA)                                   | Component solvent resistance                  | Isopropyl alcohol; 50 $^{\circ}\text{C}$ ; method 2                                                                        | No visible damage                                                                       |
| 4.30                             | 45 (XA)                                   | Solvent resistance of marking                 | Isopropyl alcohol; 50 $^{\circ}\text{C}$ ; method 1,<br>toothbrush                                                         | Marking legible;<br>no visible damage                                                   |
| 4.32                             | 21 (Ue <sub>3</sub> )                     | Shear (adhesion)                              | 45 N                                                                                                                       | No visible damage                                                                       |
| 4.33                             | 21 (Ue <sub>1</sub> )                     | Substrate bending                             | Depth 2 mm, 3 times                                                                                                        | No visible damage;<br>no open circuit in bent position<br>$\pm (0.5 \% R + 0.1 \Omega)$ |
| 4.7                              | -                                         | Voltage proof                                 | $U_{\text{RMS}} = U_{\text{ins}}$ ; 60 s                                                                                   | No flashover or breakdown                                                               |
| 4.35                             | -                                         | Flammability                                  | IEC 60695-11-5 <sup>(1)</sup> ;<br>needle flame test;<br>10 s                                                              | No burning after 30 s                                                                   |

**Note**
<sup>(1)</sup> The quoted IEC standards are also released as EN standards with the same number and identical contents.

## DIMENSIONS




| DIMENSIONS AND MASS |                |               |                             |                        |           |              |
|---------------------|----------------|---------------|-----------------------------|------------------------|-----------|--------------|
| TYPE / SIZE         | L<br>(mm)      | D<br>(mm)     | L <sub>1</sub> MIN.<br>(mm) | D <sub>1</sub><br>(mm) | K<br>(mm) | MASS<br>(mg) |
| CMB 0207            | 5.8 + 0/- 0.15 | 2.2 + 0/- 0.2 | 3.2                         | D + 0/- 0.2            | 1.1 ± 0.1 | 79           |

### Note

- Color code marking is applied according to IEC 60062 <sup>(1)</sup> in four bands (E24 series) or five bands (E96 series). Each color band appears as a single solid line, voids are permissible if at least  $\frac{2}{3}$  of the band is visible from each radial angle of view. The last color band for tolerance is approximately 50 % wider than the other bands. An interrupted brown band between the 2<sup>nd</sup> and 3<sup>rd</sup> full band indicates the special carbon film type.

## PATTERN STYLES FOR MELF RESISTORS



| RECOMMENDED SOLDER PAD DIMENSIONS |                |           |           |           |                  |           |           |           |
|-----------------------------------|----------------|-----------|-----------|-----------|------------------|-----------|-----------|-----------|
| TYPE / SIZE                       | WAVE SOLDERING |           |           |           | REFLOW SOLDERING |           |           |           |
|                                   | G<br>(mm)      | Y<br>(mm) | X<br>(mm) | Z<br>(mm) | G<br>(mm)        | Y<br>(mm) | X<br>(mm) | Z<br>(mm) |
| CMB 0207                          | 2.8            | 2.1       | 2.6       | 7.0       | 3.2              | 1.7       | 2.4       | 6.6       |

### Notes

- The rated dissipation applies only if the permitted film temperature is not exceeded. Furthermore, a high level of ambient temperature or of power dissipation may raise the temperature of the solder joint, hence special solder alloys or board materials may be required to maintain the reliability of the assembly. Specified power rating above 125 °C requires dedicated heat-sink pads, which to a great extent depend on board materials and design. The given solder pad dimensions reflect the considerations for board design and assembly as outlined e.g. in standards IEC 61188-5-x <sup>(1)</sup>, or in publication IPC-7351. They do not guarantee any supposed thermal properties, particularly as these are also strongly influenced by many other parameters.  
Still, the given solder pad dimensions will be found adequate for most general applications, e.g. those referring to “standard operation mode”. Please note however that applications for “power operation mode” require special considerations for the design of solder pads and adjacent conductor areas.

<sup>(1)</sup> The quoted IEC standards are also released as EN standards with the same number and identical contents.

**HISTORICAL 12NC INFORMATION**

- The resistors had a 12-digit numeric code starting with 2312.
- The subsequent 4 digits indicated the resistor type, specification and packaging; see the 12NC table.
- The remaining 4 digits indicated the resistance value:
  - The first 3 digits indicated the resistance value.
  - The last digit indicated the resistance decade in accordance with the 12NC Indicating Resistance Decade table.

**Last Digit of 12NC Indicating Resistance Decade**

| RESISTANCE DECADE                | LAST DIGIT |
|----------------------------------|------------|
| 1 $\Omega$ to 9.99 $\Omega$      | 8          |
| 10 $\Omega$ to 99.9 $\Omega$     | 9          |
| 100 $\Omega$ to 999 $\Omega$     | 1          |
| 1 k $\Omega$ to 9.99 k $\Omega$  | 2          |
| 10 k $\Omega$ to 99.9 k $\Omega$ | 3          |
| 100 k $\Omega$ to 999 k $\Omega$ | 4          |
| 1 M $\Omega$ to 9.99 M $\Omega$  | 5          |

**Historical 12NC Example**

The 12NC of a CMB 0207 resistor, value 47 k $\Omega$  with  $\pm 2\%$  tolerance, supplied in blister tape of 2000 units per reel was: 2312 199 24703.

**HISTORICAL 12NC - Resistor Type and Packaging**

| DESCRIPTION |           | CODE 2312 ... ..     |               |
|-------------|-----------|----------------------|---------------|
|             |           | BLISTER TAPE ON REEL |               |
| TYPE        | TOL.      | B2 2000 UNITS        | B7 7000 UNITS |
| CMB 0207    | $\pm 5\%$ | 199 3....            | 189 3....     |
|             | $\pm 2\%$ | 199 2....            | 189 2....     |
|             | $\pm 1\%$ | 199 1....            | 189 1....     |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.