




LOC		DIST		REVISIONS					
AD		00		P	LTR	DESCRIPTION	DATE	DWN	APVD
					R	REVISED PER ECO-14-000066	27JUN2014	NK	MM



RECOMMENDED HOLE LAYOUT

- 1 TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD.
- 2 THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING.
- 3 POINT OF MEASUREMENT FOR PLATING THICKNESS.
- 4 OBSOLETE PART NUMBER.
- 5 RETENTION FEATURES ON SOLDER TAILS, LOCATED AT MANUFACTURERS OPTION.
- 6 FOR 2 POSITION PART ONLY, THE NOTED DIMENSION IS .184
- 7 $\varnothing .020 \text{ M}$ FOR KINKED TAILS
- 8 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

OBSOLETE	3.284	3.200	32	66	2-104433-4
	1.784	1.700	17	36	2-104433-3
	3.484	3.400	34	70	2-104433-2
	2.184	2.100	21	44	2-104433-1
OBSOLETE	3.984	3.900	39	80	2-104433-0
	2.984	2.900	29	60	1-104433-9
OBSOLETE	2.484	2.400	24	50	1-104433-8
	1.984	1.900	19	40	1-104433-7
	1.684	1.600	16	34	1-104433-6
	1.484	1.400	14	30	1-104433-5
	1.384	1.300	13	28	1-104433-4
OBSOLETE	1.284	1.200	12	26	1-104433-3
	1.184	1.100	11	24	1-104433-2
	1.084	1.000	10	22	1-104433-1
	.984	.900	9	20	1-104433-0
OBSOLETE	.884	.800	8	18	1-104433-9
OBSOLETE	.784	.700	7	16	1-104433-8
	.684	.600	6	14	1-104433-7
	.584	.500	5	12	1-104433-6
	.484	.400	4	10	1-104433-5
	.384	.300	3	8	1-104433-4
	.284	.200	2	6	1-104433-3
	.184	.100	1	4	1-104433-2
	.084	—	—	2	1-104433-1
C	B	A	NO OF POSN	ASSEMBLY PART NUMBER	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN H MOLL 23JUN88	TE Connectivity	
DIMENSIONS: INCHES		CHK R FEJDT 23JUN88		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD R FEJDT 23JUN88	NAME	
0 PLC ± .005		PRODUCT SPEC	HEADER ASSY, MOD II, BREAKAWAY, DBL ROW, 100X.100 C	
1 PLC ± .005		APPLICATION SPEC	VERT, .025 SQ POSTS, WITH RETENTION FEATURE	
2 PLC ± .005		—	SIZE CAGE CODE DRAWING NO	
3 PLC ± .005		—	A1 00779 104433	
4 PLC ± .005		—	RESTRICTED TO	
MATERIAL: HOUSING: FLAME RETARDANT THERMOPLASTIC COLOR: BLACK		WEIGHT: —	CUSTOMER DRAWING	
FINISH: POSTS: .00015 GOLD IN CONTACT AREA .000100-.000200 WHITE TIN-LEAD ON SOLDER TAIL, ALL OVER .000500 NICKEL		SCALE: 4:1	SHEET 1 OF 1	
POST: COPPER ALLOY		REV		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[104433-6](#)