

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0039310048

Status:

Active

Overview:

Mini-Fit Jr. Power Connectors

Description:

Mini-Fit Jr. Vertical Header, 4.20mm Pitch, Dual Row, 4 Circuits, without Snap-in Plastic Peg PCB Lock, Gold, Natural

Documents:

- [3D Model](#)
- [Drawing \(PDF\)](#)
- [Product Specification PS-5556-001-001 \(PDF\)](#)
- [Application Specification AS-5557-001-001 \(PDF\)](#)
- [Packaging Specification PK-5566-000 \(PDF\)](#)
- [Packaging Specification PK-5566-003-001 \(PDF\)](#)
- [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA

LR19980

UL

E29179

General

Product Family

Series

Application

Comments

PCB Headers

5566

Power, Wire-to-Board

The 5566 header should be used with standard Mini-Fit female terminals. If increased amperage of up to 13A per circuit is needed, please consider using the Mini-Fit Plus HCS family 45750 terminals with 46015 headers; . See Molex Product specification PS-5666-001 for current de-rating information.

Overview

Product Name

UPC

Mini-Fit Jr. Power Connectors

Mini-Fit Jr.

800754256520

Physical

Breakaway

Circuits (Loaded)

Circuits (maximum)

Color - Resin

Durability (mating cycles max)

First Mate / Last Break

Flammability

Glow-Wire Capable

Guide to Mating Part

Keying to Mating Part

Lock to Mating Part

Material - Metal

Material - Plating Mating

Material - Plating Termination

Material - Resin

Net Weight

Number of Rows

Orientation

PC Tail Length

PCB Locator

PCB Retention

PCB Thickness - Recommended

Packaging Type

Pitch - Mating Interface

Pitch - Termination Interface

Plating min - Mating

No

4

4

Natural

30

No

94V-0

No

No

None

Yes

Brass

Gold

Matte Tin

Nylon

1.256/g

2

Vertical

3.50mm

Yes

None

1.60mm

Bag

4.20mm

4.20mm

0.762µm



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per - ED/61/2018 (27 June 2018)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

5566 Series

Mates With

5557 Mini-Fit Jr. Receptacle Housing

|                                                |                              |
|------------------------------------------------|------------------------------|
| Plating min - Termination                      | 2.540μm                      |
| Polarized to Mating Part                       | Yes                          |
| Polarized to PCB                               | Yes                          |
| Shrouded                                       | Fully                        |
| Stackable                                      | No                           |
| Surface Mount Compatible (SMC)                 | No                           |
| Temperature Range - Operating                  | -40° to +105°C               |
| Termination Interface: Style                   | Through Hole                 |
| <b>Electrical</b>                              |                              |
| Current - Maximum per Contact                  | 9.0A                         |
| Voltage - Maximum                              | 600V                         |
| <b>Solder Process Data</b>                     |                              |
| Duration at Max. Process Temperature (seconds) | 005                          |
| Lead-freeProcess Capability                    | WAVE                         |
| Max. Cycles at Max. Process Temperature        | 001                          |
| Process Temperature max. C                     | 260                          |
| <b>Material Info</b>                           |                              |
| Engineering Number                             | 5566-04BGS-210               |
| <b>Reference - Drawing Numbers</b>             |                              |
| Application Specification                      | AS-5557-001-001              |
| Packaging Specification                        | PK-5566-000, PK-5566-003-001 |
| Product Specification                          | PS-5556-001-001              |
| Sales Drawing                                  | SD-5566-002-000              |

This document was generated on 10/19/2018

PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[39-31-0048](#)