



LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
AD	00		H1	REVISED PER ECO-14-014232	19SEP2014	NK	MM



RECOMMENDED HOLE LAYOUT

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN
H MOLL
23-10-87

CHK
T. CLARK
23-10-87

APVD
T. CLARK
29-10-87

PRODUCT SPEC

APPLICATION SPEC

WEIGHT -

CUSTOMER DRAWING

TE Connectivity

NAME
HEADER ASSY, MOD II, BREAKAWAY,
DOUBLE ROW, .100X.100 C/L, RIGHT
ANGLE, WITH .025 SQ POSTS

SIZE
A2

CAGE CODE
00779

DRAWING NO
C=103326

RESTRICTED TO
-

SCALE
4:1

SHEET
1 OF 2

REV
H1

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± .005

4 PLC ± -

ANGLES ± -


FINISH
SEE TABLE

THIS DRAWING IS UNPUBLISHED.	RELEASED FOR PUBLICATION	- , - .
© COPYRIGHT - By -		ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
AD	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
			—	SEE SHEET 1	—	—	—

- 1 THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
- 2 POINT OF MEASUREMENT FOR PLATING THICKNESS.
- 3 ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
- 4 BREAKAWAY NOTCH ANGLE CAN BE ORIENTED TO THE RIGHT (AS SHOWN) OR TO THE LEFT
- 5 .000015 GOLD IN THE CONTACT AREA, .000100—.000200 MATTE TIN—LEAD ON THE SOLDER TAIL, ALL OVER .000050 NICKEL
- 6 .000015 GOLD IN THE CONTACT AREA, .000100—.000200 MATTE TIN ON THE SOLDER TAIL, ALL OVER .000050 NICKEL
- 7 HIGH TEMPERATURE CONFIGURATION
- 8 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

			3.984	3.900	39	80	9-103326-0		3.984	3.900	39	80	4-103326-0
			3.884	3.800	38	78	 8-103326-9		3.884	3.800	38	78	 3-103326-9
			3.784	3.700	37	76	 8-103326-8		3.784	3.700	37	76	 3-103326-8
			3.684	3.600	36	74	 8-103326-7		3.684	3.600	36	74	 3-103326-7
			3.584	3.500	35	72	 8-103326-6		3.584	3.500	35	72	3-103326-6
			3.484	3.400	34	70	8-103326-5		3.484	3.400	34	70	3-103326-5
			3.384	3.300	33	68	8-103326-4		3.384	3.300	33	68	3-103326-4
			3.284	3.200	32	66	8-103326-3		3.284	3.200	32	66	3-103326-3
			3.184	3.100	31	64	8-103326-2		3.184	3.100	31	64	3-103326-2
			3.084	3.000	30	62	8-103326-1		3.084	3.000	30	62	3-103326-1
			2.984	2.900	29	60	8-103326-0		2.984	2.900	29	60	3-103326-0
			2.884	2.800	28	58	7-103326-9		2.884	2.800	28	58	2-103326-9
			2.784	2.700	27	56	7-103326-8		2.784	2.700	27	56	2-103326-8
			2.684	2.600	26	54	7-103326-7		2.684	2.600	26	54	2-103326-7
			2.584	2.500	25	52	7-103326-6		2.584	2.500	25	52	2-103326-6
			2.484	2.400	24	50	7-103326-5		2.484	2.400	24	50	2-103326-5
			2.384	2.300	23	48	7-103326-4		2.384	2.300	23	48	2-103326-4
			2.284	2.200	22	46	7-103326-3		2.284	2.200	22	46	2-103326-3
			2.184	2.100	21	44	7-103326-2		2.184	2.100	21	44	2-103326-2
			2.084	2.000	20	42	7-103326-1		2.084	2.000	20	42	2-103326-1
			1.984	1.900	19	40	7-103326-0		1.984	1.900	19	40	2-103326-0
			1.884	1.800	18	38	6-103326-9		1.884	1.800	18	38	1-103326-9
			1.784	1.700	17	36	6-103326-8		1.784	1.700	17	36	1-103326-8
			1.684	1.600	16	34	6-103326-7		1.684	1.600	16	34	1-103326-7
			1.584	1.500	15	32	6-103326-6		1.584	1.500	15	32	1-103326-6
			1.484	1.400	14	30	6-103326-5		1.484	1.400	14	30	1-103326-5
			1.384	1.300	13	28	6-103326-4		1.384	1.300	13	28	1-103326-4
			1.284	1.200	12	26	6-103326-3		1.284	1.200	12	26	1-103326-3
			1.184	1.100	11	24	6-103326-2		1.184	1.100	11	24	1-103326-2
			1.084	1.000	10	22	6-103326-1		1.084	1.000	10	22	1-103326-1
			.984	.900	9	20	6-103326-0		.984	.900	9	20	1-103326-0
			.884	.800	8	18	5-103326-9		.884	.800	8	18	103326-9
			.784	.700	7	16	5-103326-8		.784	.700	7	16	103326-8
			.684	.600	6	14	5-103326-7		.684	.600	6	14	103326-7
			.584	.500	5	12	5-103326-6		.584	.500	5	12	103326-6
			.484	.400	4	10	5-103326-5		.484	.400	4	10	103326-5
			.384	.300	3	8	5-103326-4		.384	.300	3	8	103326-4
			.284	.200	2	6	5-103326-3		.284	.200	2	6	103326-3
			.184	.100	1	4	5-103326-2		.184	.100	1	4	103326-2
			.084			2	5-103326-1		.084			2	103326-1
REMARKS	PLATING		C	B	A	NO OF POSN	ASSEMBLY PART NUMBER	PLATING	C	B	A	NO OF POSN	ASSEMBLY PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 23-10-87 H. MOLL CHK 23-10-87 T. CLARK APVD 29-10-87 T. CLARK		 TE Connectivity	
DIMENSIONS: INCHES		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME HEADER ASSY, MOD II, BREAKAWAY, DOUBLE ROW, .100X.100 C/L, RIGHT ANGLE, WITH .025 SQ POSTS	
		0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -			
MATERIAL FINISH		WEIGHT -			
SEE TABLE		CUSTOMER DRAWING		SIZE A2 CAGE CODE 00779 DRAWING NO. C-103326	RESTRICTED TO -
				SCALE 1:1	SHEET 2 of 2
				REV H1	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[103326-6](#)