



Product: <u>19363</u> ☑

Portable Cordage, 3 C #16 Str BC, PVC Ins, PVC Jkt, UL Type SJT

Request Sample

Product Description

Portable Cordage, 3 Conductor 16AWG (65x34) Bare Copper, PVC Insulation, PVC Outer Jacket, UL Type SJT

Technical Specifications

Physical Characteristics (Overall)

Conductor No. of Conductors

BC - Bare Copper 3 Conductor Count:

Insulation

65x34

Material	Nominal Wall Thickness		
PVC - Polyvinyl Chloride	0.033 in		

Color Chart



Outer Shield Material

Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Bi-Laminate (Alum+Poly)	Beldfoil®	100%	TC - Tinned Copper	20	7x28

Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.365 in	0.047 in

Construction and Dimensions

Type of Cordage: SJT

Cabling



Electrical Characteristics

Current

Max. Recommended Current [A] 13 Amps per Conductor at 25°C (10 Amps over 50 ft) 10 Amps per Conductor at 25°C (over 50 ft)

Voltage

Dielectric Withstand Voltage UL Voltage Rating

2000 V AC Applied For 1 Min. 300 V RMS	
Electrical Characteristics Notes:	Dielectric Withstand Voltage: 2000 V AC Applied For 1 Min

Temperature Range

UL Temp Rating:	60°C	

Mechanical Characteristics

Bulk Cable Weight:	77 lbs/1000ft
--------------------	---------------

Standards

NEC/(UL) Compliance:	SJT
CSA AWM Compliance:	SJT

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

CSA Flammability:	FT2
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No	

Part Number

Variants

Item #	#	Color	Putup Type	Length	UPC
19363 010	10250	Black	Reel	250 ft	61282512700
ootnote:	:				(

History

Update and Revision:	Revision Number: 0.313 Revision Date: 08-25-2020

© 2020 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: 19363 010250