



FEATURES:

- Banana Jacks mount into panels ranging in thickness from $.063''$ (1.6mm) to $.375''$ (9.5mm).
- Model 4900 features Polypenylene Sulfide for high temperature applications.
- Model 2854 features gold plated body for optimum electrical connection.
- Model 1581 features bright tin plating

MATERIALS:

Banana Jack: Body – Brass Nickel Plated, (Model 2854, Brass, Gold Plated)

Insulators: Polycarbonate (Model 4900, High Temperature Polyphenylene Sulfide)

1/4 Internal Locking Washer: Steel, Nickel Plated

1/4-32 Hex Nut: Brass, Nickel Plated

RATINGS:

Operating Voltage: Hand-held Testing: 30VAC/60VDC Max.

Hand Free Testing in controlled Voltage Environment: 2500 WVDC.

Operating Temperature: $+115^{\circ}\text{C}$ ($+239^{\circ}\text{F}$), Model 4900 $+220^{\circ}\text{C}$ ($+428^{\circ}\text{F}$)

Current: 15 Amperes

ORDERING INFORMATION: Model #-Color Code

1581 & 2854 Std. Colors: -0 Black, -1 Brown, -2 Red, -3 Orange, -4 Yellow, -5 Green, -6 Blue, -7 Violet, -8 Gray, -9 White

4900 Std. Colors: -0 Black, -6 Blue.

Sold unassembled, in packages of 10 per color

Ordering Example: 2854-2 Gold Plated Banana Jack, Color: Red

All dimensions are in inches. Tolerances (except noted): $.xx = \pm .02''$ (.51 mm), $.xxx = \pm .005''$ (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Pomona:

[2854-8](#) [2854-4](#) [2854-1](#) [2854-0](#) [2854-6](#) [2854-9](#) [2854-5](#) [2854-2](#) [4900-0](#) [1581-02](#) [1581-6](#) [1581-8](#) [1581-4](#) [1581-9](#)
[1581-1](#) [1581-3](#) [1581-7](#) [4900-6](#)