UNCONTROLLED DOCUMENT

PART NUMBER
SSL-LX2583HD

REV.

RFV.	F.C.N. NUMBER AND REVISION COMMENTS	DATE
IVEV.	Event itember vito itevision ocimilento	DATE
ΙA	E.C.N. #10BRDR, & REDRAWN IN 3D,	l 6.14.01

 	— 5.50 [0.217]	1.80 [0.071] - 4.00 [0.157]
8.00 [0.315]		
1.00 [0.039] J	-	
27.00 [1.063] ANDDE		
	<u> </u>	
0.50 [0.020] SQR, (2 PLS,)	- 2.54 [0.100]	

ELECTRO-OPTICAL CHARACTERISTICS TA=25°C If= 20mA						
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND	
PEAK WAVELENGTH		700		nm		
FORWARD VOLTAGE		2.0	2.5	V_f		
REVERSE VOLTAGE	5.0			V_{r}	I _r =100μΑ	
AXIAL INTENSITY		6		mcd	$I_f = 20 \text{mA}$	
VIEWING ANGLE		80		2x theta		
EMITTED COLOR:	RED					
EPOXY LENS FINISH:	RED DIFFUSED					

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FÖRWARD CURRENT*	150	mA
STEADY CURRENT	25	mA
POWER DISSIPATION	120	mW
DERATE FROM 25°C	-1.2	mW/°C
OPERATING, STORAGE TEMP.	- 40 TO + 85	' C
SOLDERING TEMP.	+ 260	" C
2.0mm FROM BODY		3 SEC. MAX
4. 1. 40. 0		

^{*} t<10µS

UNCONTROLLED DOCUMENT

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.000), MIN= +DECINAL PRECISION MAX.= +0.DD MAX.= +0.DD

REV.

PART NUMBER
SSL-LX2583HD

2.5mm x 5mm RECTANGULAR, 700nm RED LED, RED DIFFUSED LENS.

CONTRIENTAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCUSSINE AND DISSEMINATION TO ALL THROU PARTIES.

RELIABILITY NOTE

dur nany years of experience data accumulation indicate that solder heat is a major cause of early and future failure. Please pay attention to your soldering process.



290 E. HELEN ROAD PALATINE, IL 60067—6976 PHONE: +1.847.359.2790

US WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY: APPROVED BY: DATE: PAGE:
BC SCALE:

PAGE: 8.27.92 PAGE: 1 OF 1 SCALE: N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSL-LX2583HD