


PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0850039043](#)
Status: **Active**
Overview: [DIN 41612](#)
Description: 2.54mm Pitch DIN 41612 C Style Male Header, Right-Angle, Through Hole, 1.10µm Selective Gold (Au) Plating, 96 Circuits, without Mounting Clips, No Flux Proof

Documents:
[Drawing \(PDF\)](#) [Packaging Specification PK-85003-001 \(PDF\)](#)
[Product Specification PS-85003-0001-001 \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification	
CSA	LR19980
UL	E29179
General	
Product Family	Backplane Connectors
Series	85003
Application	Backplane
Comments	With Mounting Clips. No Flux Proof. 4.20mm Last-Mate-First-Break Contacts. 4.80mm Normal Contacts, With Mounting Clips. No Flux Proof. 4.20mm Last-Mate-First-Break Contacts. 4.80mm Normal Contacts
Component Type	PCB Header
Overview	DIN 41612
Product Name	IEC 603-2/DIN 41612
Style	C
UPC	822350003070
Physical	
Circuits (Loaded)	96
Circuits (maximum)	96
Circuits Detail	Last-Mate-First-Break Contacts at: A:a2-a31; B:b2-b31; C:c2-c31. Standard Contacts at: X:c1,c32; Y:b1,b32; Z:a1,a32
Color - Resin	Gray
Durability (mating cycles max)	500
First Mate / Last Break	No
Flammability	94V-0
Guide to Mating Part	No
Keying to Mating Part	Yes
Material - Metal	Brass
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	Polyester
Net Weight	13.810/g
Number of Columns	16
Number of Pairs	Open Pin Field
Number of Rows	3
Orientation	Right Angle
PC Tail Length	3.00mm
PCB Locator	No
PCB Retention	Yes
PCB Thickness - Recommended	1.60mm
Packaging Type	Carton
Pitch - Mating Interface	2.54mm
Pitch - Termination Interface	2.54mm
Plating min - Mating	1.092µm



Series image - Reference only

EU ELV Not Relevant	
EU RoHS Compliant REACH SVHC Not Contained Per - ED/71/2019 (16 July 2019) Halogen-Free Status Not Low-Halogen For more information, please visit Contact US	China RoHS
China ROHS ELV RoHS Phthalates	Green Image Not Relevant Not Contained

Search Parts in this Series
[85003 Series](#)

Plating min - Termination	2.540μm
Polarized to PCB	Yes
Stackable	No
Temperature Range - Operating	-55° to +125°C
Termination Interface: Style	Through Hole
Electrical	
Current - Maximum per Contact	1.0A
Data Rate	622.0 Mbps
Voltage - Maximum	250V AC (RMS)
Solder Process Data	
Lead-freeProcess Capability	WAVE
Material Info	
Reference - Drawing Numbers	
Packaging Specification	PK-85003-001
Product Specification	PS-85003-0001-001
Sales Drawing	SD-85003-9043

This document was generated on 09/18/2019

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Molex:

85003-9043