



0.42 REF TYP

$\varnothing$	$\varnothing 0.20$	(M)	C	B	A(S)
---------------	--------------------	-----	---	---	------

MECHANICAL DRAWING OF A CONNECTOR OUTLINE. The drawing shows a rectangular connector with a grid of 12 thru holes (2 rows by 6 columns). Key dimensions and labels include:

- CONNECTOR OUTLINE**: Points to the overall shape of the connector.
- 3.5**: Dimension for the top edge of the connector.
- 1.5**: Dimension for the top edge of the connector.
- 2 TYP**: Dimension for the top edge of the connector.
- 1.5**: Dimension for the top edge of the connector.
- 6**: Dimension for the top edge of the connector.
- 3 TYP**: Dimension for the top edge of the connector.
- 2.98 REF 2 PLC**: Dimension for the top edge of the connector.
- Ø0.61 REF 5**: Dimension for the top edge of the connector.
- Ø0.15 (M) X Y**: Dimension for the top edge of the connector.
- Ø0.08 (M)**: Dimension for the top edge of the connector.
- 2 PLC**: Dimension for the top edge of the connector.
- Ø2.00 ± 0.05 THRU HOLE**: Dimension for the top edge of the connector.
- YYY**: Label for the top edge of the connector.
- Y-**: Label for the top edge of the connector.
- X-**: Label for the top edge of the connector.

—	A,D	B,C	4	5646954–5
A	B,C	D	4	5646954–4
A	C	B,D	4	5646954–3
C	B	A,D	4	5646954–2
A,B,C,D	—	—	4	5646954–1
POSITIONS LOADED WITH 10.90 REF CONTACTS	POSITIONS LOADED WITH 9.30 REF CONTACTS	POSITIONS LOADED WITH 7.68 REF CONTACTS	NO OF LOADED POSITIONS	PART NUMBER

4805 (3/11)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5646954-1](#)