



SWITCHED USB  
EXPANSION HUBS



# HUBPORT®

Industrial grade switched hubs offer instant Plug and Play USB connectivity

Hubport offers a simple solution for adding USB ports to a PC, server or thin client for instant peripheral device connectivity. This external, user installable solution plugs into a standard USB port to provide additional USB ports in a compact chassis. The switched USB architecture guarantees maximum performance on all ports simultaneously.


Models include AC or DC powered hubs that accept power from standard AC wall plugs or a range of 5.5-30 VDC power sources, such as vehicle batteries. The Industrial grade compact chassis is small enough to fit nearly anywhere. With a high USB port count, the rack mount option is perfect for data center applications.

Feature-rich design, extensive operating system support and reliable performance make Hubport ideal for mission-critical environments. Applications include connecting devices to a hub powered by car or truck battery for mobile applications; providing multiport USB connectivity in a kiosk or other compact environments; and connecting USB peripheral devices at an office workstation.

## BENEFITS

- Industrial USB 2.0 or 3.1 hubs for instant USB expansion
- Compact chassis with 4 or 7 port options
- Rack-mountable 14-port USB 2.0 model
- AC models for indoor applications
- Variable range DC models for outdoor/mobile applications
- Switched USB ensures maximum performance on all ports
- Locking or Terminal power connector on compact models
- Individual port power management

## APPLICATION EXAMPLE



## RELATED PRODUCTS



Edgeport®



AnywhereUSB








XStick USB  
Adapter



XBee 802.15.4  
Adapters

| USB FEATURES                               |   |   |  |
|--|---|---|--|
| <b>PORTS</b>                               | 7 USB 3.1 Type A  | 4 or 7 USB 2.0 Type A   | 14 USB 2.0 Type A  |
| <b>DATA RATE</b>                           | 5 Gbps  | 480 Mbps; Multi-TT switched USB architecture guarantees a full 12 Mbps simultaneously on all downstream ports, even if a high-speed 480 Mbps transfer is active |  |
| GENERAL FEATURES                           |   |   |  |
| <b>POWER</b>                               | Individual port power management; 500 mA downstream power available per port  |   |  |
| <b>OPERATING SYSTEMS</b>                   | Linux®, Windows Server 2016, Windows 10®, Windows Server® 2012, Windows 8®, Windows® 7, Windows Vista®, Windows Server® 2008, Windows XP®, Windows® XP Embedded, Windows NT® 4.0**, Windows NT Embedded**, Windows CE, Windows Server® 2003, Windows 2000 |   |  |
| <b>LEDS</b>                                | 1 System status LED<br>7 Port Status LEDs; Yellow=Full/High speed, Blue=Super Speed, Off=Port not in operation  | 1 System status LED<br>4 or 7 Port Status LEDs; Green=Port operational, Off = Port out of operation   | 1 System Status LED<br>14 Port Status LEDs; Green=Port operational, Blinking Green=Port needs attention, Off = Port not in operation |
| <b>DIMENSIONS (L X W X H) &amp; WEIGHT</b> | 2.61 in x 3.00 in x 1.00 in (6.63 cm x 7.62 cm x 2.54 cm); 6.20 oz (175.80 g)   | 2.61 in x 3.00 in x 1.00 in (6.63 cm x 7.62 cm x 2.54 cm); 6.20 oz (175.80 g)   | 4.97 in x 17.00 in x 1.74 in (12.62 cm x 43.18 cm x 4.42 cm); 35.00 oz (1134 g)  |
| <b>OTHER</b>                               | No additional IRQ or memory address requirements; Hot-swappable; 14 port is 1U Rack-Mountable (mounting ears included); Plug and Play; USB ports are backwards compatible to USB 2.0, 1.1 and 1.0   |   |  |
| POWER REQUIREMENTS                         |   |   |  |
| <b>POWER INPUT (AC MODELS)</b>             | N/A   | Ships with plug-mounted 120-230VAC 50-60 Hz at 5VDC @ 3Amps max   | Single 120-230 VAC 50/60 Hz power input IEC 60320 inlet. Max power 40W   |
| <b>POWER INPUT (DC MODELS)</b>             | Variable power DC products are 6V to 28V Max power of 35W (Terminal Block connector)  | Variable power DC products are 5.5V to 30V @ 15W (Locking Power connector pigtail included)   | N/A  |
| ENVIRONMENTAL                              |   |   |  |
| <b>OPERATING TEMPERATURE</b>               | -40°C to +70°C (-40°F to 158°F) (Industrial)  | Hubport/7c (AC model) 0°C to 55°C or Hubport/4c DC and Hubport/7c DC -40°C to +70°C   | 0°C to 55°C (32°F to 131°F)  |
| <b>RELATIVE HUMIDITY</b>                   | 0% to 95% (non-condensing)  |   |  |
| REGULATORY APPROVALS                       |   |   |  |
| <b>SAFETY</b>                              | EN60950, UL 1950, CSA 2.2 No. 950, IEC 950  |   |  |
| <b>EMISSIONS/IMMUNITY</b>                  | CE, FCC Part 15 Class B, EN55022 Class B, EN55024   |   |  |



\*Third-party support only.

\*\*Supported when connecting Digi products.

| PART NUMBERS | DESCRIPTION   |
|--------------|---|
| HP-USB-14    | Hubport/14 - 14-port USB 2.0 hub 19" rack 1U                                    |
| 301-2010-27  | Hubport/7c - 7-port switched USB 2.0 hub (Worldwide)                            |
| 301-3010-71  | Hubport/7c - USB 3.1 SuperSpeed 6-28U DC (international)                        |
| 301-1010-44  | Hubport/4c 5.5-30V DC powered USB 2.0 hub, 4 type A and 1 type B USB connectors |
| 301-1010-74  | Hubport/7c 5.5-30V DC powered USB 2.0 hub, 7 type A and 1 type B USB connectors |
| 301-3010-71  | Hubport/7c USB 3.1 SuperSpeed 6-28V DC, with terminal power connector           |

FOR MORE INFORMATION  
PLEASE VISIT [WWW.DIGI.COM](http://WWW.DIGI.COM)

**DIGI SERVICE AND SUPPORT** / You can purchase with confidence knowing that Digi is always available to serve you with expert technical support and our industry leading warranty. For detailed information visit [www.digi.com/support](http://www.digi.com/support).

© 1996-2018 Digi International Inc. All rights reserved.  
All trademarks are the property of their respective owners.

91001224  
G8/1018

**DIGI INTERNATIONAL WORLDWIDE HQ**  
877-912-3444 / 952-912-3444 / [www.digi.com](http://www.digi.com)

**DIGI INTERNATIONAL GERMANY**  
+49-89-540-428-0

**DIGI INTERNATIONAL JAPAN**  
+81-3-5428-0261 / [www.digi-intl.co.jp](http://www.digi-intl.co.jp)

**DIGI INTERNATIONAL SINGAPORE**  
+65-6213-5380

**DIGI INTERNATIONAL CHINA**  
+86-21-50492199 / [www.digi.com.cn](http://www.digi.com.cn)



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Digi International:](#)

[301-1010-34](#) [301-1010-44](#) [301-1010-74](#) [301-1010-78](#) [301-2010-24](#) [301-2010-27](#) [301-2010-36](#) [HP-USB-14-W](#)