


## High Voltage Ultrafast Rectifier



### FEATURES

- Power pack
- Glass passivated pellet chip junction
- Ultrafast recovery times
- Soft recovery characteristics
- Low switching losses, high efficiency
- High forward surge capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 245 °C (for TO-263AB package)
- Solder dip 275 °C max., 10 s per JESD 22-B106 (for TO-220AC and ITO-220AC package)
- AEC-Q101 qualified (for ITO-220AC and TO-263AB package)
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



RoHS  
COMPLIANT

### TYPICAL APPLICATIONS

For use in high voltage, high frequency power factor correctors, switching mode power supplies, freewheeling diodes and secondary DC/DC rectification application.

### DESIGN SUPPORT TOOLS

[click logo to get started](#)

**3D**  
Models  
Available

| PRIMARY CHARACTERISTICS |                                       |
|-------------------------|---------------------------------------|
| $I_{F(AV)}$             | 15 A                                  |
| $V_{RRM}$               | 500 V to 600 V                        |
| $I_{FSM}$               | 135 A                                 |
| $t_{rr}$                | 35 ns                                 |
| $V_F$ at $I_F$          | 1.5 V                                 |
| $T_J$ max.              | 150 °C                                |
| Package                 | TO-220AC, ITO-220AC, D²PAK (TO-263AB) |
| Circuit configuration   | Single                                |

### MECHANICAL DATA

**Case:** TO-220AC, ITO-220AC, D²PAK (TO-263AB)

Molding compound meets UL 94V-0 flammability rating  
Base P/N-E3 - RoHS-compliant, commercial grade  
Base P/NHE3 - RoHS-compliant, AEC-Q101 qualified

**Terminals:** matte tin plated leads, solderable per J-STD-002 and JESD22-B102

E3 suffix meets JESD 201 class 1A whisker test, HE3 suffix meets JESD 201 class 2 whisker test

**Polarity:** as marked

**Mounting Torque:** 10 in-lbs max.

| MAXIMUM RATINGS ( $T_C = 25\text{ °C}$ unless otherwise noted)                     |                |             |        |      |
|--|----------------|-------------|--------|------|
| PARAMETER  | SYMBOL         | UG15HT      | UG15JT | UNIT |
| Max. repetitive peak reverse voltage   | $V_{RRM}$      | 500         | 600    | V    |
| Max. working reverse voltage   | $V_{RWM}$      | 400         | 480    | V    |
| Max. RMS voltage   | $V_{RMS}$      | 350         | 420    | V    |
| Max. DC blocking voltage   | $V_{DC}$       | 500         | 600    | V    |
| Max. average forward rectified current (fig. 1)                                    | $I_{F(AV)}$    | 15          |        | A    |
| Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load | $I_{FSM}$      | 135         |        | A    |
| Operating junction and storage temperature range                                   | $T_J, T_{STG}$ | -55 to +150 |        | °C   |
| Isolation voltage (ITO-220AC only) from terminal to heatsink, $t = 1$ min          | $V_{AC}$       | 1500        |        | V    |



| <b>ELECTRICAL CHARACTERISTICS</b> ( $T_C = 25\text{ }^\circ\text{C}$ unless otherwise noted) |  |                                   |          |        |        |               |
|--|--|-----------------------------------|----------|--------|--------|---------------|
| PARAMETER  | TEST CONDITIONS  |                                   | SYMBOL   | UG15HT | UG15JT | UNIT          |
| Max. instantaneous forward voltage   | $I_F = 15\text{ A}$  | $T_J = 25\text{ }^\circ\text{C}$  | $V_F$    | 1.75   |        | V             |
|  |  | $T_J = 125\text{ }^\circ\text{C}$ |          | 1.50   |        |               |
| Max. DC reverse current at $V_{RWM}$   |  | $T_J = 25\text{ }^\circ\text{C}$  | $I_R$    | 30     |        | $\mu\text{A}$ |
|  |  | $T_J = 125\text{ }^\circ\text{C}$ |          | 4.0    |        | mA            |
| Max. reverse recovery time   | $I_F = 0.5\text{ A}$ , $I_R = 1.0\text{ A}$ , $I_{rr} = 0.25\text{ A}$   |                                   | $t_{rr}$ | 35     |        | ns            |
| Max. reverse recovery time   | $I_F = 1.0\text{ A}$ , $dI/dt = 50\text{ A}/\mu\text{s}$ ,<br>$V_R = 30\text{ V}$ , $I_{rr} = 0.1\text{ I}_{RM}$       |                                   | $t_{rr}$ | 50     |        | ns            |
| Typical softness factor ( $t_b/t_a$ )  | $I_F = 15\text{ A}$ , $dI/dt = 240\text{ A}/\mu\text{s}$ ,<br>$V_R = 400\text{ V}$ , $I_{rr} = 0.1\text{ I}_{RM}$      |                                   | S        | 0.9    |        | -             |
| Max. reverse recovery current  | $I_F = 15\text{ A}$ , $dI/dt = 120\text{ A}/\mu\text{s}$ ,<br>$V_R = 400\text{ V}$ , $T_C = 125\text{ }^\circ\text{C}$ |                                   | $I_{RM}$ | 9.0    |        | A             |
| Peak forward recovery time   | $I_F = 15\text{ A}$ , $dI/dt = 120\text{ A}/\mu\text{s}$ ,<br>$V_F = 1.1 \times V_F\text{ max.}$                       |                                   | $t_{fr}$ | 500    |        | ns            |

| <b>THERMAL CHARACTERISTICS</b> ( $T_C = 25\text{ }^\circ\text{C}$ unless otherwise noted) |                 |      |       |       |                           |
|---|-----------------|------|-------|-------|---------------------------|
| PARAMETER   | SYMBOL          | UG15 | UGF15 | UGB15 | UNIT                      |
| Typical thermal resistance from junction to case  | $R_{\theta JC}$ | 1.5  | 3.0   | 1.5   | $^\circ\text{C}/\text{W}$ |

**Note**(1) Pulse test: 300  $\mu\text{s}$  pulse width, 1 % duty cycle

| <b>ORDERING INFORMATIONS</b> (Example) |                              |                 |              |               |               |
|--|------------------------------|-----------------|--------------|---------------|---------------|
| PACKAGE                                | PREFERRED P/N                | UNIT WEIGHT (g) | PACKAGE CODE | BASE QUANTITY | DELIVERY MODE |
| TO-220AC                               | UG15JT-E3/45                 | 1.85            | 45           | 50/tube       | Tube          |
| ITO-220AC                              | UGF15JT-E3/45                | 1.98            | 45           | 50/tube       | Tube          |
| TO-263AB                               | UGB15JT-E3/45                | 1.35            | 45           | 50/tube       | Tube          |
| TO-263AB                               | UGB15JT-E3/81                | 1.35            | 81           | 800/reel      | Tape and reel |
| ITO-220AC                              | UGF15JT E3/45 <sup>(1)</sup> | 1.98            | 45           | 50/tube       | Tube          |
| TO-263AB                               | UGB15JT E3/45 <sup>(1)</sup> | 1.35            | 45           | 50/tube       | Tube          |
| TO-263AB                               | UGB15JT E3/81 <sup>(1)</sup> | 1.35            | 81           | 800/reel      | Tape and reel |

**Note**

(1) AEC-Q101 qualified, available in ITO-220AC and TO-263AB package



### RATINGS AND CHARACTERISTICS CURVES ( $T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)




Fig. 1 - Forward Current Derating Curve




Fig. 4 - Typical Reverse Leakage Characteristics




Fig. 2 - Max. Non-Repetitive Peak Forward Surge Current




Fig. 5 - Typical Junction Capacitance




Fig. 3 - Typical Instantaneous Forward Characteristics





Fig. 6 - Reverse Switching Characteristics




### PACKAGE OUTLINE DIMENSION in inches (millimeters)


#### TO-220AC




#### ITO-220AC



#### D<sup>2</sup>PAK (TO-263AB)



#### Mounting Pad Layout





## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Vishay:](#)

[UG15JT/45](#) [UGB15JT-E3/81](#) [UG15HT/45](#) [UG15HT-E3/45](#) [UG15HTHE3/45](#) [UG15JT-E3/45](#) [UG15JTHE3/45](#)  
[UGF15HT-E3/45](#) [UGF15JT-E3/45](#) [UGF15HTHE3/45](#) [UGF15JTHE3/45](#)