	П		LOC DIST	DIST REVISIONS 安更 P LTR DESCRIPTION DATE DWN A								
	ALL RIGHTS RESERVED.		J	P LTR							ATE DWN	
				F	REVISED	PER ECR-	-11-0013	310		214	PR11   T.	Г <u> </u> Т.М.
					٨	16	40	7-	<b>√</b> −6	7_ 2	M ————————————————————————————————————	
				720	999-5	12	50	7-	-2	7-	-2	
			SS		٨	24	25	5-	-4	5-	-4	
			) -TO-B) TH BOSS			22	30	5-	-2	5-	-2	
			対基板接続用) :ンブリ ;シブリ ;ector (BーT TYPE WITH			20	30	5-	-0	5-	-0	
			7ヶ(基板対基板接続用) - アッセンブリ 基板位置決め用ボス付 CONNECTOR (B-			18	35	4-	-8	4-	-8	
			コネクタ ッダー 7 イブ 基板 -P CO -SS'Y &			16	40	4-	-6	4-	-6	
			_ ``			14	45	4-	-4	4-	-4	
						12	50	4-	-2	4-	-2	
			商ビケー サーフ PACKA ROW			10	60	4-	-0	4-	-0	
			TUBE	720999-4		6	90	3-	-6	3_2	<del>-6</del>	
					Λ	20	30	2-	-0	2-	-0	
						16	40	1-	-6	1-	-6	
JED.				2-912050-0		14	45	1-174	821-4	1-175	643-4	
PUBLISE	By -		名称 NAME		塩ビケース 型番		数 量 (ケ)	(1)	7 タ型番 ラ状) 	コネク	ァース詰	
NN S					E P/N	Pos.	QTY'S	CONN P	/N (L/P)	IN TUI	BE P/N	
'HIS DRAWING IS UNPUBLISHED.	COPYRIGHT	注記 1. 包装規格: 107-5123-2 NOTES 1. PACKAGING SPEC: 107-5123-2										
THIS	0		2 OBSOL			J 12J-Z						
	•	DIMENSIONS: 単位: 粍 mm	,WA									
TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差  CHR S.KIKUCHI APVD N.ONOUE					30MAY88 30MAY88	4	TE Connectivity					
1— 2—	SFC SFC	士 士 10を招え 30以 士 30を据え100以	PRODUCT SPEC 製品規格 UT: ±0.25 UT: ±0.3			NAME 名称 TUBE PACKAGING 1.25 F-P CONNECTOR (B-TO-B)						
3 PLC     ±     APLICATION SPEC     DOUBLE ROW F       4 PLC     ±       ANGLES     ±   APPLICATION SPEC  BY BIZE  CAGE CODE DRAW  THE STATE OF THE STA								POST HDR ASS'Y SMT TYPE WITH BOSS ING NO RESTRICTED TO				
1111			WEIGHT			4 007		<b>-</b> 1756	43			_
		Ψ -	CUSTOME	STOMER DRAWING				SCAL 尺度	_E	SHEET 1	of 1	rev F

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: