


UZZT 4.5mmL Chip Type, Wide Temperature Range




- Chip type with 4.5mm height, operating over wide temperature range of -40 to +105°C.
- Designed for surface mounting on high density PC board.
- Applicable to automatic mounting machine fed with carrier tape.
- Compliant to the RoHS directive (2011/65/EU).
- AEC-Q200 compliant. Please contact us for details.


Specifications

Item	Performance Characteristics																								
Category Temperature Range	-40 to +105°C																								
Rated Voltage Range	6.3 to 50V																								
Rated Capacitance Range	1 to 100μF																								
Capacitance Tolerance	±20% at 120Hz, 20°C																								
Leakage Current	After 2 minutes' application of rated voltage at 20°C, leakage current is not more than 0.01CV or 3 (μA), whichever is greater.																								
Tangent of loss angle (tan δ)	Measurement frequency : 120Hz at 20°C																								
	Rated voltage (V)	6.3	10	16	25	35	50																		
Stability at Low Temperature	Measurement frequency : 120Hz																								
	Rated voltage (V)	6.3	10	16	25	35	50																		
	Impedance ratio ZT / Z20 (MAX.)	Z-25°C / Z+20°C	6	5	3	3	3	3																	
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 1000 hours at 105°C.		<table border="1"> <tr> <td>Capacitance change</td> <td colspan="2">Within ±25% of the initial capacitance value (16V or less)</td> <td colspan="3">Within ±20% of the initial capacitance value (25V or more)</td> </tr> <tr> <td>tan δ</td> <td colspan="2">300% or less than initial specified value</td> <td colspan="3">Less than or equal to the initial specified value</td> </tr> <tr> <td>Leakage current</td> <td colspan="2">Less than or equal to the initial specified value</td> <td colspan="3">Less than or equal to the initial specified value</td> </tr> </table>					Capacitance change	Within ±25% of the initial capacitance value (16V or less)		Within ±20% of the initial capacitance value (25V or more)			tan δ	300% or less than initial specified value		Less than or equal to the initial specified value			Leakage current	Less than or equal to the initial specified value		Less than or equal to the initial specified value		
	Capacitance change	Within ±25% of the initial capacitance value (16V or less)		Within ±20% of the initial capacitance value (25V or more)																					
	tan δ	300% or less than initial specified value		Less than or equal to the initial specified value																					
Leakage current	Less than or equal to the initial specified value		Less than or equal to the initial specified value																						
Shelf Life	After storing the capacitors under no load at 105°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the specified values for the endurance characteristics listed above.																								
Resistance to soldering heat	The capacitors are kept on a hot plate for 30 seconds, which is maintained at 250°C. The capacitors shall meet the characteristic requirements listed at right when they are removed from the plate and restored to 20°C.		<table border="1"> <tr> <td>Capacitance change</td> <td colspan="2">Within ±10% of the initial capacitance value</td> </tr> <tr> <td>tan δ</td> <td colspan="2">Less than or equal to the initial specified value</td> </tr> <tr> <td>Leakage current</td> <td colspan="2">Less than or equal to the initial specified value</td> </tr> </table>					Capacitance change	Within ±10% of the initial capacitance value		tan δ	Less than or equal to the initial specified value		Leakage current	Less than or equal to the initial specified value										
	Capacitance change	Within ±10% of the initial capacitance value																							
	tan δ	Less than or equal to the initial specified value																							
Leakage current	Less than or equal to the initial specified value																								
Marking	Black print on the case top.																								

Chip Type



Type numbering system (Example : 16V 10μF)



Dimensions

Cap. (μF)	Code	6.3		10		16		25		35		50	
		0J	1A	1C	1E	1V	1H						
1	010											4	5.4
2.2	2R2											4	9.6
3.3	3R3											4	12
4.7	4R7							4	11	4	13	5	16
10	100					4	16	5	20	5	22	6.3	26
22	220	4	19	5	24	5	26	6.3	33	6.3	36		
33	330	5	26	5	30	6.3	35	6.3	42				
47	470	5	32	6.3	40	6.3	44						
100	101	6.3	52										

Rated ripple current (mA rms) at 105°C 120Hz

Frequency coefficient of rated ripple current

Frequency	50 Hz	120 Hz	300 Hz	1 kHz	10 kHz or more
Coefficient	0.70	1.00	1.17	1.36	1.50

- Taping specifications are given in page 23.
- Recommended land size, soldering by reflow are given in page 18, 19.
- Please select UUX(p.158), UUU(p.164) series if high C/V products are required.
- Please refer to page 3 for the minimum order quantity.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Nichicon:

[UZS1V4R7MCL1GB](#) [UZT1H100MCL1GB](#) [UZT1V100MCL1GB](#) [UZT1V220MCL1GB](#) [UZT0J101MCL1GB](#)
[UZT0J220MCL1GB](#) [UZT0J330MCL1GB](#) [UZT0J470MCL1GB](#) [UZT1A220MCL1GB](#) [UZT1A330MCL1GB](#)
[UZT1A470MCL1GB](#) [UZT1C100MCL1GB](#) [UZT1C220MCL1GB](#) [UZT1C330MCL1GB](#) [UZT1C470MCL1GB](#)
[UZT1E100MCL1GB](#) [UZT1E220MCL1GB](#) [UZT1E330MCL1GB](#) [UZT1E4R7MCL1GB](#) [UZT1H010MCL1GB](#)
[UZT1H0R1MCL1GB](#) [UZT1H2R2MCL1GB](#) [UZT1H3R3MCL1GB](#) [UZT1H4R7MCL1GB](#) [UZT1HR22MCL1GB](#)
[UZT1HR33MCL1GB](#) [UZT1HR47MCL1GB](#) [UZT1V4R7MCL1GB](#)