

COIL: @ 25°C

RESISTANCE 200 OHMS ± 10%

NOMINAL VOLTAGE 6.0 VDC

MUST OPERATE 3.4 VDC

MUST RELEASE 2.0 VDC MAX, 0.28 VDC MIN.

ENVIRONMENT:

VIBRATION 10 CPS TO 3000 CPS @ 30 g's

SHOCK 75 g's 6 MS. DURATION


TEMPERATURE -65 °C TO +125 °C

NOTES: OPERATE TIME 4.0 MS MAX

RELEASE TIME 7.5 MS MAX

CONTACT STABILIZATION 2.5 MS MAX.

CUSTOMER DATA SHEET



CONTACT RATING: LOW LEVEL TO 1 AMP  
28 VDC RESISTIVE 100,000 OPERATIONS MIN

DR. R.B 12/19/97 *CK* *ERRY* 12/19/97

**COMMUNICATIONS**  
**INSTRUMENTS, INC.**

CUST. QPL  
CUST. NO. M39016/42-050P

TYPE JMGSD RELAY

**JMGSCD-6PW**

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[JMGSCD-6PW](#)