Blanking Foam Strips



Full Length Blanking Shade

specifications

Blanking foam strips shall be used to minimize gaps in and around network cabinets and prevent bypass air to improve energy efficiency and optimize the cooling system in Cold Aisle Containment (CAC) or Vertical Exhaust Duct (VED) applications. The blanking foam strips shall be adhesive-backed foam and conform to a large variety of non-standard configurations, especially those smaller than one rack unit.



technical information

Material:	1/16" (1.6mm) thick closed-cell vinyl foam
Adhesive properties:	Removable and repositionable acrylic-based adhesive on paper release liner
Temperature/ humidity range:	50°F – 158°F (10°C – 70°C); 60% relative humidity
RoHS compliance:	Yes
Packaging:	4.00" (101.6mm) x 100.00" (2540.0mm) roll of product with perforations

key features and benefits

Prevents bypass airflow	Suitable to seal inconsistently sized openings that do not conform to standard blanking solutions		
Removable/ repositionable adhesive	Prevents residue on network equipment when adhesive-backed foam is removed		
Closed cell vinyl foam material	Durable foam product withstands application environment to allow safe installation within the data center		
Perforation design	Perforations provided every 1.00" (25.4mm) in width and 20.00" (508.0mm) in length to eliminate the need for tools in common applications		
Color	Black		

applications

Suitable in preventing recirculated or bypass air in cabinets where sealing of air gaps is critical to the function of network equipment. The blanking foam strips are typically installed in CAC or VED applications to improve efficiency of these solutions. This blanking foam strip product can be stacked, folded, rolled, or manipulated in ways that allow the product to seal various size openings that are not typically filled by tool-less blanking panels or other blanking options.

4 – 45 consecutive rack units:	FLBSIM-Y
Tool-Less Blanking Pa	anels
1 RU x 19" (483mm) width for 3/8" square holes:	TLBP1S-V
2 RU x 19" (483mm) width for 3/8"	TEDI 13-V
square holes:	TLBP2S-V
1 RU x 19" (483mm) width for round holes:	TLBP1R-V
2 RU x 19"(483mm) width for	
round holes:	TLBP2R-V
Cool Boot® Raised Fl	
Grommet (Surface M	
6" x 8":	RFG6X8SMY
8" x 8":	RFG8X8SMY
10" x 8":	RFG10X8SMY
12" x 4":	RFG12X4SMY
12" x 8":	RFG12X8SMY
4.5" diameter:	RFG3DSMY
6.5" diameter:	RFG5DSMY
Cool Boot® Raised Fl Grommet (Integral Mo	•
6" x 8":	RFG6X8Y
8" x 8":	RFG8X8Y
10" x 8":	RFG10X8Y
10 x 8 : 12" x 4":	RFG12X4Y
12 x 4 . 12" x 8":	RFG12X8Y
12 x o : 4.5" diameter:	RFG3DY
<i>6.5" diameter:</i>	RFG5DY RFG5DY

Blanking Foam Strips

Blanking Foam Strip Dimensions



Ordering Information

Part Number	Part Description	Color	Length In. (mm):	Width In. (mm):
BFS100X2000	Adhesive-backed foam strips, 1/16" (1.6mm) closed-cell vinyl foam, perforated to create multiples of 1.00" (25.4mm) x 20.00" (508.0mm) strips.	Black	100.00 (2540.0)	4.00 (101.6)

Dimensions are in inches. [Dimensions in brackets are metric].

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA Markham, Ontario cs-cdn@panduit.com Phone: 800.777.3300

PANDUIT EUROPE LTD. London, UK cs-emea@panduit.com Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD. Republic of Singapore cs-ap@panduit.com Phone: 65.6305.7575

PANDUIT JAPAN Tokyo, Japan cs-japan@panduit.com Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA Guadalajara, Mexico cs-la@panduit.com Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD. Victoria, Australia cs-aus@panduit.com Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

For more information



Visit us at www.panduit.com

©2013 Panduit Corp. ALL RIGHTS RESERVED. RKSP124--WW-ENG 1/2013

Contact Customer Service by email: cs@panduit.com or by phone: 800.777.3300

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit: BFS100X2000