



**Product: 8524** ☑

Lead Wire, #22 Str TC, PVC Ins, TYPE MW MIL-W-76C-PVC 1000V 80C

# **Product Description**

Low Temp Plastic Lead Wire, 22AWG (7x30) Tinned Copper, PVC Insulation, TYPE MW MIL-W-76C-PVC 1000V 80C

#### **Technical Specifications**

#### **Physical Characteristics (Overall)**

#### Conductor

AWG	Stranding	Material	No. of Conductors
22	7x30	TC - Tinned Copper	1
Condu	uctor Count:	1	

#### Insulation

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.064 in	0.017 in

## **Electrical Characteristics**

# Conductor DCR

Nominal Conductor DCR
15 Ohm/1000ft

#### Current

Element	Max. Recommended Current [A]
Single conductor in free air @ 30C ambient	9.0 A

# Voltage

Description	Voltage Rating [V]
Mil-W-76C	1000 V

# **Temperature Range**

Non-UL Temp Rating:	80°C
Operating Temp Range:	-40°C To +80°C

## **Mechanical Characteristics**

	Bulk Cable Weight:	3.6 lbs/1000ft
--	--------------------	----------------

# Standards

UL AWM Style:	N/A
Military Specification:	MIL-W-76C type MWP

# **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes

EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-10-01
MII Order #39 (China RoHS):	Yes

#### Flammability, LS0H, Toxicity Testing

UL voltage rating:
--------------------

#### Plenum/Non-Plenum

Plenum (Y/N):
---------------

#### **Part Number**

#### Variants

Item #	Color	Putup Type	Length	UPC
8524 010100	Black	Reel	100 ft	612825212379
8524 0101000	Black	Reel	1,000 ft	612825347873
8524 0131000	Blue, Dark	Reel	1,000 ft	612825212393
8524 006100	Blue, Light	Reel	100 ft	612825212256
8524 0061000	Blue, Light	Reel	1,000 ft	612825212263
8524 001100	Brown	Reel	100 ft	612825212119
8524 0011000	Brown	Reel	1,000 ft	612825212126
8524 008100	Gray	Reel	100 ft	612825212300
8524 0081000	Gray	Reel	1,000 ft	612825212317
8524 005100	Green, Dark	Reel	100 ft	612825212232
8524 0051000	Green, Dark	Reel	1,000 ft	612825212249
8524 003100	Orange	Reel	100 ft	612825212171
8524 0031000	Orange	Reel	1,000 ft	612825212188
8524 002100	Red	Reel	100 ft	612825212157
8524 0021000	Red	Reel	1,000 ft	612825347866
8524 007100	Violet	Reel	100 ft	612825212287
8524 0071000	Violet	Reel	1,000 ft	612825212294
8524 009100	White	Reel	100 ft	612825212348
8524 0091000	White	Reel	1,000 ft	612825212355
8524 004100	Yellow	Reel	100 ft	612825212201
8524 0041000	Yellow	Reel	1,000 ft	612825212218

Footnote:

P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'.

#### **History**

Update and Revision:	Revision Number: 0.279 Revision Date: 04-28-2020

## © 2020 Belden, Inc

#### All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.