

Single Contact Candelabra Bayonet

11 SERIES

- SINGLE CONTACT CANDELABRA BAYONET GROUNDED LAMPHOLDERS
- 6" WIRE LEAD • ELECTRO-TINNED PLATED STEEL SHELL
- MAXIMUM RATING: 25 WATTS, 12 VOLTS

Overview

The 11 Series lampholders are constructed with a electro-tinned plated steel shell with a brass center contact mounted on a phenolic insulating disc with one 6" wire lead. The brackets are grounded to the shell. Lampholders are designed for use in low voltage lamp applications with single contact candelabra bayonet lamps.

Specifications

Shell: electro-tinned plated steel.

Custom shells also available:

Single contact indexed shell: add **-DX** to end of part number. For example, **11-207** changes to **11-207-DX** for indexed shell. Shell is only available in zinc plated steel.

Brass Shell: add **-BR** to the end of a part number. For example, **11-207** changes to **11-207-BR** for brass shell.

Center contact: nickel plated brass supplied with phenolic insulating disc.

Custom contact also available.

Glass Melamine Center Contact: for outdoor environments.

Spring: zinc plated steel. A custom stainless steel spring is also available.

Wire leads: 6" lead: #18 AWG, black, bare copper, PVC insulated, UL/CSA rated 105° C, stripped 1/2". Grounded units are supplied with one 6" wire lead. Custom wire lengths, stripping, termination and wire types are also available.


Second ground wire: White #18AWG, attached to the spring. Add **-2W** to end of part number to order.

Mounting: Brackets: 0.025" to 0.032" zinc plated steel. Custom brackets and plating types are available. **Plug button** and **threaded bushing** (supplied hex nut and lockwasher) also available.

Maximum rating: 25 Watts, 12 Volts.


Grounded only.

11-207



Grounded only.

11-230BN



Suggested Mounting Hole 13/32" Diameter.

Can't find it here? We have many more standard and custom solutions


For further information, phone Customer Service at 800.522.5546.

Single Contact Candelabra Bayonet

11 SERIES

Maximum Rating: 25 Watts, 12 Volts

Electro-Tinned Plated Steel Shell
Grounded
6" Wire Lead




Single Contact Candelabra Bayonet

11 SERIES

Maximum Rating: 25 Watts, 12 Volts

Electro-Tinned Plated Steel Shell
Grounded
6" Wire Lead









Single Contact Candelabra Bayonet

11 SERIES

Maximum Rating: 25 Watts, 12 Volts

Electro-Tinned Plated Steel Shell
Grounded
6" Wire Lead

11-240XT  1-5/32" O.D. 31/32" 21/32" DIA. Plug button: zinc plated steel, for 15/16" hole with panel thickness range 1/32" to 5/64". Grounded only.	11-245  15/32" 21/32" O.D. 31/32" 1/32" 3/4" 5/8" Grounded only.
11-255  21/32" O.D. 15/32" 23/32" 31/32" 1/32" 3/4" Grounded only.	11-260  21/32" O.D. 1-1/2" 9/16" 1/32" 3/16" 11/64" 3/8" 7/8" 1/2" 11/64" HOLE DIA. Grounded only.
11-272  11/16" 21/32" O.D. 63/64" 3/64" 15/16" 3/8" 3/16" 1/4" 11/64" HOLE DIA. 11/64" 5/8" For reversed bracket: Grounded unit: 11-271. Grounded only.	11-275  21/32" O.D. 63/64" 3/64" 11/64" HOLE DIA. 3/8" 3/16" 5/8" 1-7/8" Grounded only.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

VCC:

11-208