

EzFlex™ Thermo-Anemometer



Air Velocity Meter

With flexible 16" gooseneck probe

Features:

- Remote vane extends on 16" (406mm) gooseneck for easy access into hard to reach areas
- Selectable air velocity units of ft/min, m/s, km/hr, MPH, and Knots
- Ideal when reaching into an air duct or other HVAC applications
- 3% basic accuracy
- Temperature measurements displayed in °F or °C
- Large dual 9999 count backlit display
- Data hold function allows user to freeze the displayed value
- MAX/MIN records and displays highest and lowest readings
- Auto power off and low battery indication
- Complete with battery and hard carrying case



Thermo-Anemometers

Extech's Thermo-Anemometers with remote sensors are the most popular models for HVAC applications.

Units	Range	Resolution	Basic Accuracy
ft/min	80 to 5900ft/min	1	±3% rdg±40 ft/min
m/s	0.40 to 30.00m/s	0.01	±3% rdg±0.20 m/s
km/hr	1.4 to 108.0km/hr	0.1	±3% rdg±0.8 km/h
MPH	0.9 to 67.0 MPH	0.1	±3% rdg±0.4 MPH
Knots	0.8 to 58.0 Knots	0.1	±3% rdg±0.4knots
Temperature	32 to 122°F (-0 to 50.0°C)	0.1°	±4°F/±2°C
Dimensions	6.42 x 1.77 x 1.34" (163 x 45 x 34mm) meter 1.8"D (46mm) vane		
Weight	7.4oz (210g)		

Ordering Information:

EZ30EzFlex™ Thermo-Anemometer



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Extech:](#)

[EZ30](#)