XZCPA0566L10

pre-wired connectors XZ - straight female - M8 - 3 pins - cable PUR 10m

Product availability: Non-Stock - Not normally stocked in distribution facility



Main	
Commercial Status	Commercialised
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Pre-wired connectors
Series name	Application
Electrical connection	Straight female connector M8, 3 pins
Collar material	Stainless steel 316L
Status LED	Without
Cable length	32.81 ft (10 m)

Complementary

Cable connector fixing	Screw-on	
Cable outer diameter	0.2 in (5 mm)	
Cable composition	3 x 0.34 mm²	
Wire insulation material	PUR	
[Ue] rated operational voltage	60 V AC	
[In] rated current	4 A	
Contact resistance	<= 5000 μOhm	
Insulating resistance	>= 1 GΩ	
Product weight	0.75 lb(US) (0.34 kg)	

Environment

IP degree of protection	IP68
Ambient air temperature for operation	-13185 °F (-2585 °C) (static)
Ambient air temperature for storage	-31212 °F (-35100 °C)

Ordering and shipping details

22483 - MACHINE CABLES
DS3
003389119021586
1
0.79
Non-Stock - Not normally stocked in distribution facility
N
DE

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0601 - Schneider Electric declaration of conformity

Contractual warranty

Period	18 months

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XZCPA0566L10