



No. of pos.	A <sup>-0,76</sup>	B <sup>+0,25</sup>	C	D <sup>-0,3</sup>
9	31,19	16,79	25,00 <sup>+0,12 -0,10</sup>	6,12
15	39,52	25,12	33,30 <sup>+0,15</sup>	6,12
25	53,42	38,84	47,04 <sup>±0,13</sup>	5,99
37	69,70	55,30	63,50 <sup>+0,13 -0,11</sup>	5,99

Directive 2002/95/EC  
„RoHS“  
Compliant

Part No. for socket connector		
No. of pos.	UNC 4-40	M 3
9	16-000280	16-000230
15	16-000290	16-000240
25	16-000300	16-000250
37	16-000310	16-000260

NOTES:

- METALSHELLS: COPPER ALLOY; min. 315µin TIN over 40-80µin NICKEL
- THREADED INSERT: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
- COLLAR: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
- JACKSCREW: STAINLESS STEEL 1.4305
- WIRE ROPE: STAINLESS STEEL 1.4401
- RETAINING WASHER: STAINLESS STEEL 1.4122
- TERMINAL RING: UNINSULATED, COPPER ALLOY; min. 200µinTIN over 80µin NICKEL
- MAXIMUM TORQUE VALUE FOR THREAD: 6in.LB
- CONNECTOR IS PART MARKED: PART NO. CONEC ABC

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

CUSTOMER APPROVAL DATE:

NAME: \_\_\_\_\_ TITLE: \_\_\_\_\_

COMPANY NAME: \_\_\_\_\_

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

1 x b	Ä 3186	17.11.2008	Petker
a	Origin		
rev.	description	date	name

tolerance ISO 2768-m	dim. in mm	scale: 2:1 (5:1)
date	name	material: SEE NOTES
drawn 30.04.08 Sonnenberg	appd. 30.04.08 Fischer	norm
d-old		title: <b>SCREEN CAP</b> 9-37pos. FOR SOCKET CONNECTOR with threaded insert, jackscrew and wire rope
dwg no: Inventor 10		DIN-A3
part no: 16K1A2276		sh: 1
part no: see table		

**CONEC**

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[CONEC:](#)

[16-000300](#) [16-000280](#) [16-000290](#) [16-000310](#)