

Metal Can Type Crystals HC-49S AS Series



Features

- Wide operating temperature range.
- Superior and reliable performance in harsh environment.
- RoHS Compliant / Pb Free

Electrical Specifications

| Item / Type | AS |
|--|---------------------------------|
| Frequency Range | 4 ~ 25 MHz |
| Overtone | Fundamental |
| Frequency Tolerance (at 25 °C) | ± 30 ppm |
| Frequency Stability Over Operating Temperature Range | ± 30 ppm Max. |
| Operating Temperature Range | - 40 ~ +85 °C |
| Drive Level | 10 μW (typical) ; 300 μW (Max.) |
| Load Capacitance | 12 pF, or specify |
| Storage Temperature Range | - 40 ~ +85 °C |
| Reliability Standard | AEC-Q200 VER.C |

Equivalent Series Resistance(ESR)

| Fundamental | |
|-------------|------------|
| 4 ~ 6 MHz | 150 Ω Max. |
| 6 ~ 8 MHz | 120 Ω Max. |
| 8 ~ 10 MHz | 80 Ω Max. |
| 10 ~ 12 MHz | 70 Ω Max. |
| 12 ~ 16 MHz | 60 Ω Max. |
| 16 ~ 25 MHz | 50 Ω Max. |

Dimensions



Units: mm

Remark : Specification subject to change without prior notice. Please confirm with our sales.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TXC Corporation:](#)

[AS-13.560MAHE-B](#) [AS-28.63636MAHE-B](#) [AS-4.194304MAHE-B](#) [AS-4.000MAHK-B](#) [AS-11.2896MAHK-B](#) [AS-13.22563MAHKB](#) [AS-16.000MAHK-B](#) [AS-8.000MAHK-B](#) [AS-10.000MAHI-B](#) [AS-14.31818MAHI-B](#) [AS-16.9344MAHH-B](#) [AS-20.500MAHQ-T](#) [AS-3.579545MAHE-B](#) [AS-12.000MDHK-B](#) [AS-3.579545MDHE-B](#) [AS-16.9344MAGH-B](#) [AS-4.000MEHK-B](#) [AS-16.000MAGE-B](#) [AS-10.000MDHI-B](#) [AS-4.000MAHH-B](#) [AS-11.0592MAHI-B](#) [AS-12.000MAQL-B](#) [AS-4.000MAGJ-B](#) [AS-8.000MAGE-B](#) [AS-14.31818MDHI-B](#) [AS-4.000MDHK-B](#) [AS-4.000MDGJ-B](#) [AS-13.560MDIE-B](#) [AS-8.000MAHI-B](#) [AS-11.2896MAGQ-B](#) [AS16000001](#) [AS-13.225625MAHK-B](#) [AS-20.500MAHQ-B](#)