



1. THIS CONNECTOR ASSEMBLY IS SUPPLIED WITH Be Cu CONTACT RETENTION CLIPS INSTALLED IN THE INSERT ASSEMBLY.
2. THIS CONNECTOR ASSEMBLY MATES WITH ANY PLUG CONNECTOR WITH THE SAME INSERT ARRANGEMENT AND DIMENSIONAL REQUIREMENTS PER MIL-C-24308.
3. MARKED WITH .047 [1.19]-.062 [1.57] HIGH CHARACTERS. FAR SIDE REFERS TO THE WIDE SIDE OF THE KEYSTONE. NEAR SIDE REFERS TO THE NARROW SIDE OF THE KEYSTONE.
4. MAXIMUM WIRE INSULATION TO BE USED WITH THIS CONNECTOR ASSEMBLY IS .068 [1.73] DIAMETER.
5. SPECIAL REQUIREMENTS PER BOEING 1A01 DOCUMENT.
6. BUILT TO ORDER, NO INVENTORY OF THIS PART NUMBER IS TO BE KEPT. SINGLE LOT DATE CODE REQUIRED.



	1AO1-027PHW	1-211639-1
	--	211639-4
	1AO1-027PHA	211639-1
	CUSTOMER MARKING	PART NUMBER
REMARKS	TE Connectivity	
	PLUG ASSY.,AMPLIMITE,15 POSN.,SIZE 2, SERIES 109 WITH GROMMET	
THIS DRAWING IS A CONTROLLED DOCUMENT.	13FEB09	
BY P. YEAGER	13FEB09	
FOR R. LEASE	13FEB09	
DIMENSIONS: INCHES [mm]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	
0 PLC	± -	
1 PLC	± -	
2 PLC	± -	
3 PLC	± .005 [0.13]	
4 PLC	± -	
MATERIAL	FINISH	
	WEIGHT	
	A1 00779 C 211639	
	CUSTOMER DRAWING	
	SCALE 4:1	
	1 OF 1	
	REV J	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[211639-4](#)