


COIL: @ 25°C	
RESISTANCE	800 OHMS ± 10%
NOMINAL VOLTAGE	12.0 VDC
GATE TURN-ON	4.3 VDC MAX.
GATE TURN-OFF	0.5 VDC MAX.
MUST OPERATE	7.1 VDC
MUST RELEASE	4.0 VDC MAX, 0.65 VDC MIN.

ENVIRONMENT:			
VIBRATION	10	CPS TO	3000
		CPS @	30
		g's	
SHOCK	75	g's	6
		MS. DURATION	
TEMPERATURE	-65	°C TO	+125
		°C	

NOTES:	
OPERATE TIME	4.0 MS MAX.
RELEASE TIME	7.5 MS MAX.
CONTACT BOUNCE	1.5 MS MAX.

CUSTOMER DATA SHEET



CONTACT RATING: LOW LEVEL TO 1A
28 VDC RESISTIVE 100,000 OPERATIONS

DR. R.B. 11/19/97 CK. *[Signature]*

COMMUNICATIONS INSTRUMENTS, INC.

CUST. _____	QPL	"JMGST" RELAY
CUST. NO. M28776/7-010L	REV. _____	

JMGST-12LW

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[JMGST-12LW](#)