

Replacement die - CRIMPFOX-M RC 10/DIE - 1212077

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(<http://phoenixcontact.com/download>)



Die, for Crimpfox-M, for non-insulated cable lugs 4 - 10 mm², packed in a serial storage box



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	68.2 g
Custom tariff number	82032000
Country of origin	Sweden

Technical data

Dimensions

Length (b)	114 mm
Width (a)	75 mm
Height	25.5 mm

General

Color	black
Compression	Indent crimp
Type of contact	Non-insulated cable lugs
Designation	Crimping position 1
Max. cross section	4 mm ²
AWG max	12
Designation	Crimping position 2
Max. cross section	6 mm ²
AWG max	10
Designation	Crimping position 3
Max. cross section	10 mm ²

Replacement die - CRIMPFOX-M RC 10/DIE - 1212077

Technical data

General

AWG max	8
---------	---

Classifications

eCl@ss

eCl@ss 4.0	21040301
eCl@ss 4.1	21040301
eCl@ss 5.0	21040301
eCl@ss 5.1	21040301
eCl@ss 6.0	21043811
eCl@ss 7.0	21043811
eCl@ss 8.0	21049090

ETIM

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001282
ETIM 5.0	EC001282

UNSPSC

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Replacement die - CRIMPFOX-M RC 10/DIE - 1212077

Approvals

Approval details

EAC

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact:

1212077