






RECOMMENDED HOLE LAYOUT

1. ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
2. TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
3. THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
4. HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK.
5. FINISH: 0.000381 [.000015] GOLD ON CONTACT AREA,
0.00254-0.00508 [.000100-.000200] MATTE TIN-LEAD ON SOLDER TAIL,
0.00127 [.000050] NICKEL ENTIRE POST.
6. FINISH: 0.000381 [.000015] GOLD ON CONTACT AREA,
0.00254-0.00508 [.000100-.000200] MATTE TIN ON SOLDER TAIL,
0.00127 [.000050] NICKEL ENTIRE POST.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIM 190CT2006 R BROWN CHK 190CT2006 J GESFORD		 TE Connectivity	
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 0.05[.002] 2 PLC ± - 0.13[.005] 3 PLC ± - 4 PLC ± - ANGLES ± -		NAME APVD 190CT2006 J GESFORD PRODUCT SPEC — APPLICATION SPEC —	
		SIZE A1		CAGE CODE 00779	
MATERIAL 		DRAWING NO C-146509		RESTRICTED TO —	
FINISH SEE TABLE		WEIGHT —		SCALE 4:1 SHEET 1 OF 2 REV A	
CUSTOMER DRAWING					

8

7

6

5

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

LOCAD

DIST00

REV

DATE

BY

APP

DESCRIPTION

DATE

BY

APP

SEE SHEET 1

—

—

—

△₆	101.19 [3.984]	99.06 [3.900]	39	80	9—146509—0
△₆	98.65 [3.884]	96.52 [3.800]	38	78	8—146509—9
△₆	96.11 [3.784]	93.98 [3.700]	37	76	8—146509—8
△₆	93.57 [3.684]	91.44 [3.600]	36	74	8—146509—7
△₆	91.03 [3.584]	88.90 [3.500]	35	72	8—146509—6
△₆	88.49 [3.484]	86.36 [3.400]	34	70	8—146509—5
△₆	85.95 [3.384]	83.82 [3.300]	33	68	8—146509—4
△₆	83.41 [3.284]	81.28 [3.200]	32	66	8—146509—3
△₆	80.87 [3.184]	78.74 [3.100]	31	64	8—146509—2
△₆	78.33 [3.084]	76.20 [3.000]	30	62	8—146509—1
△₆	75.79 [2.984]	73.66 [2.900]	29	60	8—146509—0
△₆	73.25 [2.884]	71.12 [2.800]	28	58	7—146509—9
△₆	70.71 [2.784]	68.58 [2.700]	27	56	7—146509—8
△₆	68.17 [2.684]	66.04 [2.600]	26	54	7—146509—7
△₆	65.63 [2.584]	63.50 [2.500]	25	52	7—146509—6
△₆	63.09 [2.484]	60.96 [2.400]	24	50	7—146509—5
△₆	60.55 [2.384]	58.42 [2.300]	23	48	7—146509—4
△₆	58.01 [2.284]	55.88 [2.200]	22	46	7—146509—3
△₆	55.47 [2.184]	53.34 [2.100]	21	44	7—146509—2
△₆	52.93 [2.084]	50.80 [2.000]	20	42	7—146509—1
△₆	50.39 [1.984]	48.26 [1.900]	19	40	7—146509—0
△₆	47.85 [1.884]	45.72 [1.800]	18	38	6—146509—9
△₆	45.31 [1.784]	43.18 [1.700]	17	36	6—146509—8
△₆	42.77 [1.684]	40.64 [1.600]	16	34	6—146509—7
△₆	40.23 [1.584]	38.10 [1.500]	15	32	6—146509—6
△₆	37.69 [1.484]	35.56 [1.400]	14	30	6—146509—5
△₆	35.15 [1.384]	33.02 [1.300]	13	28	6—146509—4
△₆	32.61 [1.284]	30.48 [1.200]	12	26	6—146509—3
△₆	30.07 [1.184]	27.94 [1.100]	11	24	6—146509—2
△₆	27.53 [1.084]	25.40 [1.000]	10	22	6—146509—1
△₆	24.99 [.984]	22.86 [.900]	9	20	6—146509—0
△₆	22.45 [.884]	20.32 [.800]	8	18	5—146509—9
△₆	19.91 [.784]	17.78 [.700]	7	16	5—146509—8
△₆	17.37 [.684]	15.24 [.600]	6	14	5—146509—7
△₆	14.83 [.584]	12.70 [.500]	5	12	5—146509—6
△₆	12.29 [.484]	10.16 [.400]	4	10	5—146509—5
△₆	9.75 [.384]	7.62 [.300]	3	8	5—146509—4
△₆	7.21 [.284]	5.08 [.200]	2	6	5—146509—3
△₆	4.67 [.184]	2.54 [.100]	1	4	5—146509—2
△₆	2.13 [.084]	—	—	2	5—146509—1
PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER

△₅	101.19 [3.984]	99.06 [3.900]	39	80	4—146509—0
△₅	98.65 [3.884]	96.52 [3.800]	38	78	3—146509—9
△₅	96.11 [3.784]	93.98 [3.700]	37	76	3—146509—8
△₅	93.57 [3.684]	91.44 [3.600]	36	74	3—146509—7
△₅	91.03 [3.584]	88.90 [3.500]	35	72	3—146509—6
△₅	88.49 [3.484]	86.36 [3.400]	34	70	3—146509—5
△₅	85.95 [3.384]	83.82 [3.300]	33	68	3—146509—4
△₅	83.41 [3.284]	81.28 [3.200]	32	66	3—146509—3
△₅	80.87 [3.184]	78.74 [3.100]	31	64	3—146509—2
△₅	78.33 [3.084]	76.20 [3.000]	30	62	3—146509—1
△₅	75.79 [2.984]	73.66 [2.900]	29	60	3—146509—0
△₅	73.25 [2.884]	71.12 [2.800]	28	58	2—146509—9
△₅	70.71 [2.784]	68.58 [2.700]	27	56	2—146509—8
△₅	68.17 [2.684]	66.04 [2.600]	26	54	2—146509—7
△₅	65.63 [2.584]	63.50 [2.500]	25	52	2—146509—6
△₅	63.09 [2.484]	60.96 [2.400]	24	50	2—146509—5
△₅	60.55 [2.384]	58.42 [2.300]	23	48	2—146509—4
△₅	58.01 [2.284]	55.88 [2.200]	22	46	2—146509—3
△₅	55.47 [2.184]	53.34 [2.100]	21	44	2—146509—2
△₅	52.93 [2.084]	50.80 [2.000]	20	42	2—146509—1
△₅	50.39 [1.984]	48.26 [1.900]	19	40	2—146509—0
△₅	47.85 [1.884]	45.72 [1.800]	18	38	1—146509—9
△₅	45.31 [1.784]	43.18 [1.700]	17	36	1—146509—8
△₅	42.77 [1.684]	40.64 [1.600]	16	34	1—146509—7
△₅	40.23 [1.584]	38.10 [1.500]	15	32	1—146509—6
△₅	37.69 [1.484]	35.56 [1.400]	14	30	1—146509—5
△₅	35.15 [1.384]	33.02 [1.300]	13	28	1—146509—4
△₅	32.61 [1.284]	30.48 [1.200]	12	26	1—146509—3
△₅	30.07 [1.184]	27.94 [1.100]	11	24	1—146509—2
△₅	27.53 [1.084]	25.40 [1.000]	10	22	1—146509—1
△₅	24.99 [.984]	22.86 [.900]	9	20	1—146509—0
△₅	22.45 [.884]	20.32 [.800]	8	18	146509—9
△₅	19.91 [.784]	17.78 [.700]	7	16	146509—8
△₅	17.37 [.684]	15.24 [.600]	6	14	146509—7
△₅	14.83 [.584]	12.70 [.500]	5	12	146509—6
△₅	12.29 [.484]	10.16 [.400]	4	10	146509—5
△₅	9.75 [.384]	7.62 [.300]	3	8	146509—4
△₅	7.21 [.284]	5.08 [.200]	2	6	146509—3
△₅	4.67 [.184]	2.54 [.100]	1	4	146509—2
△₅	2.13 [.084]	—	—	2	146509—1
PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:

mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± —

1 PLC ± 0.5[.02]

2 PLC ± 0.13[.005]

3 PLC ± —

4 PLC ± —

ANGLES ± —

MATERIAL

4

SEE TABLE

DWN R BROWN 19OCT2006

CHK J GESFORD 19OCT2006

APVD J GESFORD 19OCT2006

PRODUCT SPEC

APPLICATION SPEC

WEIGHT —

CUSTOMER DRAWING

NAME

SIZE CAGE CODE DRAWING NO

RESTRICTED TO

TE Connectivity

HEADER ASSEMBLY, MOD II, STACKING, DOUBLE ROW, .025 SQ.POST, UNSHROUDED

A100779146509

SCALE 4:1 SHEET 2 OF 2 REV A1

4805 (3/11)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[6-146509-3](#)