

Printed-circuit board connector - DFK-PC 4/ 2-G-7,62-FS4,8 BK - 1753488

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Feed-through header, nominal current: 15 A, number of positions: 2, pitch: 7.62 mm, connection method: Solder/Slip-on connection, color: black, contact surface: Tin

The figure shows a 5-pos. version of the product

Your advantages

- ✓ Space-saving, standardized slip-on connection allows worldwide use
- ✓ Cable connection on the inside of the device enables flexible positioning of the panel feed-through



Key Commercial Data

Packing unit	50 pc
GTIN	
GTIN	4046356326445

Technical data

Dimensions

Pitch	7.62 mm
Dimension a	7.62 mm

General

Range of articles	DFK-PC 4/...-G -FS4,8
Number of positions	2
Connection method	Solder/Slip-on connection
Rated voltage (III/3)	400 V
Connection in acc. with standard	EN-VDE
Nominal current I_N	15 A
Nominal cross section	4 mm ²

Connection data

Printed-circuit board connector - DFK-PC 4/ 2-G-7,62-FS4,8 BK - 1753488

Technical data

Connection data

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	4 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	10

Standards and Regulations

Connection in acc. with standard	EN-VDE
	CSA

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

CSA / EAC / cULus Recognized

Ex Approvals

Approval details

CSA		http://www.csagroup.org/services-industries/product-listing/	13631
	B	C	
Nominal voltage UN	300 V	300 V	
Nominal current IN	20 A	20 A	

EAC		B.01742
-----	---	---------

Printed-circuit board connector - DFK-PC 4/ 2-G-7,62-FS4,8 BK - 1753488

Approvals

cULus Recognized  http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E60425-19920722		
	B	C
Nominal voltage UN	300 V	300 V
Nominal current IN	20 A	20 A

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1753488](#)