


# Manual Switches

## Power Duty Paddle

### AML33/35 Series

#### INCANDESCENT, NEON, OR NON-LIGHTED DISPLAY



Colored housing covers ordered separately.

#### CONTACT ARRANGEMENT

1 or 2 poles: Form A



Electrical Data	page 19
Paddle Covers	page 47
Lamps	page 58
Mounting Dimensions	page 60

#### FEATURES

- Toggle type paddle operators permanently installed in rectangular housings.
- 2-position maintained action.
- AML33 lamp circuit independent of switch circuit.
- UL recognized, CSA certified.



\*AML33 Series: 2-pole only.  
\*AML35 Series: 1-pole and 2-pole.

#### AML33 ORDER GUIDE

AML33 accepts one incandescent lamp which can be furnished installed or ordered separately.

AML33 E	B	A	4	AA	01
<b>Housing Type</b> AML33 E Rectangular Non-Lighted	<b>Operator/Bezel Color</b> B Black/Black	<b>Incandescent Lamp Type</b> A No Lamp Installed B 6 V Lamp* C 14 V Lamp* E 28 V Lamp*	<b>Terminal Type</b> 4 .187 x .020 (Solder or Quick-Connect)	<b>Circuitry Codes</b> Silver Contacts: AA 1-Pole (One Form A Single-throw, Normally-Open) AC 2-Pole (Two Form A)	<b>Operating Action</b> 01 Maint. ON      Maint. OFF
AML33 F Rectangular 1 Lamp Ckt.	Lamp ① →				

\* Lamps will be installed per each lamp circuit specified in the Housing Type.

#### AML35 ORDER GUIDE

AML35 has neon lamp wired to 125 or 250 VAC resistor.

AML35 F	B	B	4	AA	01
<b>Housing Type</b> AML35 F Rectangular 1 Neon Lamp	<b>Operator/Bezel Color</b> B Black/Black	<b>Neon Lamp Voltage</b> Red 125 VAC C 250 VAC Green 125 VAC P 250 VAC	<b>Terminal Type/ Lamp Circuit †</b> 4 .187 x .020 (Solder or Quick-Connect) With Isolated Lamp Circuit 7 .187 x .020 With Integral Lamp Circuit (Available with 2-Pole devices only)	<b>Circuitry Codes</b> Silver Contacts: AA (One Form A Single-Throw) Available only with isolated lamp circuit, term. type 4. AC 2-Pole (Two Form A)	<b>Operating Action</b> 01 Maint. ON      Maint. OFF
Lamp ① →					

① The "MICRO SWITCH" identification is shown on this side of the switch housing.

Example: **AML35FBB4AA01**

Rectangular paddle switch housing;  
black paddle and bezel; 125 VAC neon  
lamp; .187 x .020 terminals with isolated

lamp circuit; 1-Pole Form A Single-Throw;  
with circuit ON in one extreme position  
and OFF in the other (maintained).

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Honeywell](#):

[AML35FBB4AA01](#) [AML35FBB4AC01](#) [AML35FBB7AC01](#) [AML35FBC4AC01](#) [AML35FBC7AC01](#) [AML33EBA4AA01](#)  
[AML33EBA4AC01](#) [AML33FBA4AC01](#)