

NUMBER C-177901





三角法 (3rd ANGLE PROJECTION)

METRIC

単位: mm DIMENSIONS IN MM. DO NOT SCALE PRINT

PRINT DIST

ロックタイプII
LOCK TYPE II



ピッチ (PITCH)
3.96
7.92

表1 (TABLE 1)

トレードマーク (TRADE MARK)	生産場所 (MANUFACTURING PLACE)
—AMP OR AMP	日本 (JAPAN)
—+AMP OR AMP	中国 (CHINA(PCR))
*AMP OR AMP	韓国 (KOREA)

NOTES, 1. PRODUCT SPEC, 108-5410

2. APPLICABLE CONTACT P/N

REC CONTACT: 177915-□ (×20- 15AWG)
177914-□ (×26- 22AWG)

3. MATING CONN, P/N

CAP HSG: 177909-□ (PANEL MOUNT)
TAB CONTACT: 177917-□ (×20- 15AWG)
177916-□ (×26- 22AWG)

4. APPLICABLE PLATE P/N: 177919-□

5. INSTRUCTION SHEET, 411-5638

△ SEE TABLE 1

7. ALL PARTS MEET RTI ELECTRICAL RATING OF 105C ACCORDING TO UL 1977
8. PART 1-177901-5 MEET BELOW REQUIREMENT
MATERIAL: NYLON UL 94-V0 BLACK
MAXIMUM RATING TEMPERATURE 150C




9. PART 5-177901-1 COMPLY WITH GLOW WIRE REQUIREMENT FOR PARTS OF NON-METALLIC MATERIAL SUPPORTING A CURRENT-CARRYING CONNECTION DETAILED IN IEC 60335-1, SECTION 30 (GWT)

R5	REVISED PER ECR-13-019881	A.Z	D.Z	23DEC12
R4	REVISED PER ECR-12-013854	A.Z	F.M	02AUG12
R3	REVISED PER ECR-12-010818	A.Z	F.M	14JUN12
R2	REVISED PER ECR-12-010382	A.Z	F.M	07JUN12
R1	REVISED PER ECO-11-005140	RK	HMR	01APR11
LTR	変更 (REVISION RECORD)	DR	CHK	DATE

LOCK TYPE I	自然色 (NATURAL)	6	5-177901-1
ロックタイプII LOCK TYPE II	青 (BLUE)	6	3-177901-6
	自然色 (NATURAL)	6	3-177901-1
ロックタイプ LOCK TYPE	ハウジング色調 (HOUSING COLOR)	極数 (Pos.)	型番 (P/N)

ロックタイプI LOCK TYPE I	黒 (BLACK)	6	1-177901-5
	青 (BLUE)	↑	↑ -6
	黄 (YELLOW)	↑	↑ -4
	赤 (RED)	↓	↓ -2
	自然色 (NATURAL)	6	177901-1
ロックタイプ LOCK TYPE	ハウジング色調 (HOUSING COLOR)	極数 (Pos.)	型番 (P/N)

本図ロックタイプIを示す
AS SHOWN LOCK TYPE I



TE Connectivity

適合電線範囲 (WIRE RANGE)	絶縁外皮 (INSULATION DIA.)	名称 (NAME)	AMP POWER DOUBLE LOCK CONN.
mm ² (AWG)	mmφ	6極 3.96mmピッチ プラグハウジング (2列タイプ)	
材料 (MATERIAL)	仕上 (FINISH)	AMP POWER DOUBLE LOCK CONN. 3.96mm PITCH PLUG HOUSING 6 Pos (DBL ROW)	
6/6 NYLON (UL94V-0)	—	一般公差	SIZE LOC 番号 (No.)
DR. 9. SEP '93 M. SUZUKI	DE. 9. SEP '93 M. SUZUKI	10以下: ±0.2 10を超え 30以下: ±0.25 30を超え 100以下: ±0.3 角 度: ±3°	A3 J C-177901
CHK. 9. SEP '93 M. SHINDO	APP. 9. SEP '93 Y. KASHIWA	尺貫 (SCALE)	REV. R5 SHEET 1 OF 1

CUSTOMER DRAWING

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[3-177901-6](#)