





NUMBER C-5917628  
METRIC  
③ 角法 (3rd ANGLE PROJECTION)



注記:  
 ① 材料:ハウジング;熱可塑性樹脂 (UL 94V-0) 色:黒  
 コンタクト:銅合金  
 ② 表面仕上げ:  
 コンタクト:全面ニッケル下地めっき  
 接触部金めっき、脚部すずめっき  
 3. 本製品はフラックス上がり防止処理済み

NOTE:  
 ① MATERIAL:HOUSING;THERMOPLASTICS (UL 94V-0) BLACK  
 CONTACT:COPPER ALLOY  
 ② FINISH:CONTACT:Au AT CONTACT AREA  
 TIN AT TINE, OVER Ni  
 3. THESE PRODUCTS WERE COATED BY ANTI-FLUX MIGRATION AGENT.



④	29	36.83	49	62.23	—	102.87	38.83	64.23	104.87	107.86	115.49	0.76µm	160	2	7
④	—	—	—	—	39	49.53	—	—	51.53	54.62	62.15	0.76µm	80	2	3
④	39	49.53	49	62.23	—	115.57	51.53	64.23	117.57	120.66	128.19	0.3µm	180	—	8
④	29	36.83	49	62.23	—	102.87	38.83	64.23	104.87	107.86	115.49	0.3µm	160	—	7
④	29	36.83	39	49.53	—	90.17	38.83	51.53	92.17	95.26	102.79	0.3µm	140	—	6
④	19	24.13	39	49.53	—	77.47	26.13	51.53	79.47	82.56	90.09	0.3µm	120	—	5
④	—	—	—	—	49	62.23	—	—	64.23	67.32	74.85	0.3µm	100	—	4
④	—	—	—	—	39	49.53	—	—	51.53	54.62	62.15	0.3µm	80	—	3
④	—	—	—	—	29	36.83	—	—	38.83	41.92	49.45	0.3µm	60	—	2
④	—	—	—	—	19	24.13	—	—	26.13	29.22	36.75	0.3µm	40	—	1
	a	A	b	B	c	C	D	E	F	G	H	THK OF GOLD	Pos.		P/N

PRINT DIST  
 単位: ㎜ DIMENSIONS IN MM. DO NOT SCALE PRINT  
 AMP-J010-2C  
 REV. 3/93

				<b>TE</b> TE Connectivity	
A REVISED PER ECR-12-013341		28MAR2013	K.M.E.T		名称 (NAME) AMP FH CONNECTOR RECEPTACLE (VERTICAL) FOR 8mm STACKING
O RELEASED (FJBO-0582-04)		08JUN04	T.K.I.E		
LTR DESCRIPTION		DATE	DWN	APVD	一般公差 (GENERAL TOLERANCE) 10以下: ±0.2 10以上 30以下: ±0.25 30以上 100以下: ±0.3 角 度: ±3°
CHK. I.ENOMOTO		09JUN04	APP. I.ENOMOTO		材料 (MATERIAL) ①
					仕上 (FINISH) ②
					寸法 (SCALE) NTS
					REV. A
					番号 (No.) C-5917628
					SHEET 1 OF 1

(CUSTOMER DRAWING) 参考 面

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5917628-1](#)