



PART NUMBER	LDS-CA14RI REV.	В
DATE	E.C.N. NUMBER AND REVISION COMMENTS	REV.
05.12.97	E.C.N. #10342.	Α
04.22.98	E.C.N. #10BRDR. & REDRAWN.	В










DIGIT DETAIL



ELECTRO-OPTICAL	CHARACTERISTI	ICS TA = 25°C	$I_f = 20 \text{mA}$		
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		635 (RED)		nm	
FORWARD VOLTAGE		4.0/2.0	5.0/2.5	$V_f$	
REVERSE VOLTAGE	5.0			$V_r$	I <sub>r</sub> =100uA
AXIAL INTENSITY		9800		mcd	I <sub>f</sub> =20mA
EMITTED COLOR:	RED				
FACE COLOR:	GRAY				
EPOXY LENS FINISH	H: MILKY	WHITE DIFFUS	SED		

LIMITS OF SAFE OPERATION AT 25°C	PER CHIP	
PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	-1. <u>2</u>	mW/⁺C
OPERATING TEMP.	-20 TO +85	•C
STORAGE TEMP.	-20 TO +85	•c
SOLDERING TEMP.	+260	.c
2.0mm FROM BODY		3 SEC. MAX
* +<10c		

\* t<10uS

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION UNCONTROLLED DOCUMENT



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.6538

\*\*THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.\*\*

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

1.0" SINGLE DIGIT, SEVEN SEGMENT DISPLAY, 635nm RED, GREY FONT/WHITE SEGMENTS, COMMON CATHODE.

DATE: 05.01.96 DRAWN BY: MA PAGE: 1 OF CHKD BY: KF KF SCALE: NTS APRVD BY: UNIT: mm [INCH] (Pb)

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:
LDS-CA14RI