



| Band Size | Circumference | |
|-----------|---------------|-------------|
| | Min. | Max. |
| Small | 5.5" (140mm) | 9" (229mm) |
| Medium | 6" (152mm) | 11" (279mm) |
| Large | 7" (178mm) | 12" (305mm) |

| Item | Band Size | Coil Cord |
|----------------------|-----------|------------------------------|
| 2225 | Small | Not Included |
| 2226 | Medium | Not Included |
| 2227 | Large | Not Included |
| 2228 | Small | 6' (2234) |
| 2229 | Medium | 6' (2234) |
| 2230 | Large | 6' (2234) |
| 2231 | Small | 12' (2235) |
| 2232 | Medium | 12' (2235) |
| 2233 | Large | 12' (2235) |

Unless otherwise noted, tolerance $\pm 10\%$

Specifications and procedures subject to change without notice.

- A. .002" polyphenylsulfone sheet laminated to each link. Provides >5,000 Volt RMS insulation per ASTM D149. Will not flake or peel.
- B. Unique dual contact design is to be paired with a [SCS MagSnap™ 360 Coil Cord](#) (not included) for a superior electrical connection. The magnetic connection made with the coil cord maintains a 1-5 pound perpendicular breakaway force to prevent accidental disconnects.
- C. Black ABS plastic cap. Molded with "MagSnap 360" trademark.
- D. Underwriters Laboratory Listing 90P1C.
- E. Inside links are constructed of 300 Series Stainless Steel. Width of links is 0.63".
- F. Black ABS plastic insulator separates band into halves.

Meets required limits of ANSI/ESD S20.20 and requirements of ANSI/ESD S1.1.

U.S. Patent Pending

MAGSNAP 360™ DUAL-WIRE METAL EXPANSION WRISTBAND

926 JR Industrial Drive, Sanford, NC 27332
 WEB SITE: StaticControl.com
 PHONE (919) 718-0000

DRAWING NUMBER
2225

DATE
August 2015



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[SCS:](#)

[2225](#)