

PDM: Rev:L STATUS: Released Printed: May 19, 2011

				1			2						3	}		4			
ſ	TIN LE			LEAD-FI	LEAD-FREE PART NUMBER								1						
	PART NUMBER / CONTACT LOADING								PART NUMBER / CONTACT LOADING										
	DIM-P ±0.10 P/N AND PERFORMANCE LEVEL							DIM-P ±0.10				P/N AND PERFORMANCE LEVEL				RECOMMENDED PCB LAYOUT PER 12MM LENGTH			
	ROW-A	ROW-B	ROW-C	ROW-D	TRAY PACKAGING	TUBE PACKAGING	SP N°	ROW-A	ROW-B	ROW-C	ROW-D	1	TRAY PACKAGING	TUBE PACKAGING	SP Nº				
	5.00	5.00	5.00	5.00	HM1L43ADP000H6F	HM1L43ADP000H6		5.00	5.00	5.00	5.00		HM1L43ADP000H6PLF	HM1L43ADP000H6LF					
А	5.75	5.75	5.75	5.75	HM1L43LDP000H6F	, ,		5.75	5.75	5.75	5.75		HM1L43LDP000H6PLF				А		
	6.50	6.50	6.50	6.50	HM1L43DDP000H6F	,		6.50	6.50	6.50	6.50		HM1L43DDP000H6PLF						
	6.50	5.00	5.00	5.00	HM1L43BDP000H6F	,		6.50	5.00	5.00	5.00		HM1L43BDP000H6PLF						
	6.50	5.75	5.75	6.50	HM1L43CDP000H6F	>		6.50	5.75	5.75	6.50		HM1L43CDP000H6PLF		1				
	5.00	5.00	6.50	5.00	HM1L43ZDP110H6F		110	5.00	5.00	6.50	5.00		HM1L43ZDP110H6PLF		110				
_	5.00	5.75	6.50	5.00	HM1L43ZDP430H6F		430	5.00	5.75	6.50	5.00		HM1L43ZDP430H6PLF		430				
	5.00	5.75	5.00	5.00	HM1L43ZDP448H6F	,	448	5.00	5.75	5.00	5.00		HM1L43ZDP448H6PLF		448				
																<u>3±0.15</u> 6/			
	5.75	5.00	5.00	5.00	HM1L43ZDP009H6F	,	009	5.75	5.00	5.00	5.00		HM1L43ZDP009H6PLF		009				
р	5.75	6.50	5.75	5.00	HM1L43ZDP424H6F	,	424	5.75	6.50	5.75	5.00		HM1L43ZDP424H6PLF		424	Hole according to product spec	В		
В																GS-12-445 (for press-fit) ,			
																GS-12-446 (for STB)			
	6.50	5.75	6.50	5.75	HM1L43ZDP037H6F	>	037	6.50	5.75	6.50	5.75		HM1L43ZDP037H6PLF		037				
	6.50	5.75	5.00	5.75	HM1L43ZDP102H6F	>	102	6.50	5.75	5.00	5.75		HM1L43ZDP102H6PLF		102				
	6.50	6.50	6.50	5.75	HM1L43ZDP135H6F	>	135	6.50	6.50	6.50	5.75		HM1L43ZDP135H6PLF		135				
	6.50	5.75	5.75	5.75	HM1L43ZDP369H6F	>	369	6.50	5.75	5.75	5.75		HM1L43ZDP369H6PLF		369				
	8.00	6.50	6.50	6.50	HM1L43ZDPA07H6F		A07	8.00	6.50	6.50	6.50		HM1L43ZDPA07H6PLF		A07				
С																	С		
S	STANDARD	STANDARD MATING LENGTHS = 5.75 (AND 5.00-6.50)									STANDARD MATING LENGTHS = 5.75 (AND 5.00-6.50)								
	DET.	AIL OF CE	ENTRAL PE	G SCALE 8/1	L														
	0.35		~~~~	1	DETAIL	OF LOCATING PEGS (2x)	SCALE 8/1										L		
FCI.	<u> </u>			<u>}</u>			00/122 0/ 1												
L L	, ↓ 1.1 1.1				. •	I ALLAN									European Views				
Copyright	• [±] S								surface							tolerance std projection	1		
bhu	~		╧┽		1								Dr CHAMPION 1994/04/05			ES UNLESS OTHERWISE SPECIFIED			
				Ø1.95_0.05	ו א						-								
D	<u>R:0.30</u>	- ·		-		/ <u>/</u> \	±0.05		rev ec		ir de HA 2003,	ate /03/17	Eng LENOIR	1994/04/05 ^{AI}		LINEAR 0.XX ±0.1 A3 4	D		
	<u></u>				-i	₹. / /\ \ ▼	/ K		H LSO		LE 2005,	/06/06	Chr LEGARE		xx* ±2* Product f	0.XXX ±0.1 ECN LS08-0125 Samily METRAL Spec ref -			
		Ŕ		-	⊠ <u>1.70</u> ^{±0.05}						GO 2006	/0//12					1		
	\$0.5 ^{*0.1}								K LS07-0184 MLE 2007/07/24 L LS08-0125 MLE 2008/05/13				FCI, METRAL RA HDR WB			1000000000000000000000000000000000000			
		╼┤		2.25 REF /	<u>^</u>	-1	ŀ				- V V 4X24 CTS - PF - PUSH PE			PUSH PE	- CUSTOMER sheet 2 of 2				
L	REV F	- 2006-04	-17						-		<u> </u>						I		

1

2

3PDM: Rev:L STATUS: Released

Printed: May 19, 2011

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

FCI / Amphenol:

<u>HM1L43ADP000H6PLF</u> <u>HM1L43DDP000H6PLF</u> <u>HM1L43LDP000H6PLF</u> <u>HM1L43ZDP009H6PLF</u> HM1L43ADP000H6LF