

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
AD	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		K2		REVISED PER ECO-11-004917	11MAR11	RK	HMR

CONTACTS ARE LATCHED INTO THE PRELOAD WINDOWS

USE WITH #26-#30 AWG WIRE SIZE, .054/.030 INSULATION DIAMETER, .015 MAXIMUM INSULATION THICKNESS

THE DIMENSION APPLIES WITH THE FORWARD PRELOAD STOP IN CONTACT WITH THE HOUSING SURFACE

POINT OF MEASUREMENT FOR PLATING THICKNESS

FOR INDIVIDUAL ASSEMBLIES SEE PART NUMBER 103897

ASSEMBLIES ARE JOINED BY THE CARRIER STRIP. ORDER QUANTITY REFLECTS TOTAL NUMBER OF INDIVIDUAL ASSEMBLIES REQUIRED. SEE TABLE FOR NUMBER OF ASSEMBLIES PER STRIP.

POINT OF MEASUREMENT FOR PLATING THICKNESS (INSIDE BEAMS)

MAXIMUM ALLOWABLE BOW OF ASSEMBLY NOT TO EXCEED .055.

.000030 GOLD IN THE CONTACT AREA, .000050-.000100 BRIGHT TIN-LEAD ON THE TERMINATION AREA, ALL OVER .000050 NICKEL.

.000030 GOLD IN THE CONTACT AREA, .000050-.000100 MATTE TIN ON THE TERMINATION AREA, ALL OVER .000050 NICKEL.

OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

11	OBSOLETE	10	2	2.40	1.198	1-104257-1	12	-6-103961-4
11	OBSOLETE	10	2	2.20	1.098	1-104257-0	11	-6-103961-0
		10	2	2.00	.998	104257-9	10	5-103961-9
		10	2	1.80	.898	104257-8	9	5-103961-8
		10	2	1.60	.798	104257-7	8	5-103961-7
		10	2	1.40	.698	104257-6	7	5-103961-6
		10	4	2.39	.598	104257-5	6	5-103961-5
		10	4	1.99	.498	104257-4	5	5-103961-4
		10	5	1.99	.398	104257-3	4	5-103961-3
		10	8	2.40	.298	104257-2	3	5-103961-2
		10	10	2.00	.198	104257-1	2	5-103961-1
11	OBSOLETE	9	2	2.40	1.198	1-104257-1	12	-1-103961-4
11	OBSOLETE	9	2	2.20	1.098	1-104257-0	11	-1-103961-0
		9	2	2.00	.998	104257-9	10	103961-9
		9	2	1.80	.898	104257-8	9	103961-8
		9	2	1.60	.798	104257-7	8	103961-7
		9	2	1.40	.698	104257-6	7	103961-6
		9	4	2.39	.598	104257-5	6	103961-5
		9	4	1.99	.498	104257-4	5	103961-4
		9	5	1.99	.398	104257-3	4	103961-3
		9	8	2.40	.298	104257-2	3	103961-2
		9	10	2.00	.198	104257-1	2	103961-1
		6		B	A	HOUSING PART NUMBER	NO OF POSN	ASSEMBLY PART NUMBER ON STRIP

EXAMPLE: STRIP ASSEMBLY
SCALE 3:1

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		DWN		CHK		APVD		NAME	
INCHES		0 PLC	± -	L A MAYER		11-4-86		J SCHIEFFER		RCPT ASSY, AMPMODU MTE, SINGLE ROW, .100 C/L	
		1 PLC	± -	P de Jong		11-12-86		108-25034		ROW, .100, LATCHED & POLARIZED,	
		2 PLC	± .02	J SCHIEFFER		11-13-86		114-25026		FOR #26-#30 AWG WIRE SIZE, STRIP FORM	
		3 PLC	± .005	PRODUCT SPEC				WEIGHT		RESTRICTED TO	
		4 PLC	± -	APPLICATION SPEC				SCALE		SHEET	
		ANGLES	± -	FINISH				CUSTOMER DRAWING		REV	
			± -	SEE TABLE				SCALE 4:1		SHEET 1 of 1	
								SCALE 4:1		REV K2	

1471-9 (3/11)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[103961-4](#)