



STYLE I

8-321235-5	2.625	.860	NATURAL	CLEANED	I	LOOSE PC, BOX SPL	100	600	300
8-321235-1	2.625	.860	NATURAL	CLEANED		LOOSE PC, BOX	100	600	300
3-321235-0	2.625	1.151	BLACK		I	LOOSE PC	1000		
1-321235-1	2.625	1.151	NATURAL		I	LOOSE PC	1000	600	300
1-321235-0	2.625	1.151	NATURAL	CLEANED		LOOSE PC	1000	600	300
321235	2.093	.860	NATURAL	CLEANED		LOOSE PC	1000	300	300
PART NO.	DIM 'A'	DIM 'B'	COLOR	FINISH	STYLE	PACKAGE TYPE	QTY	FILE E66717 LR7189 Certified	
								MAX VOLTAGE RATING	

- TIN PLATE PER ASTM B545.
- PRELIMINARY - NOT FOR PRODUCTION.

WIRE SPLICE	SEE TABLE	INSULATION: PVC COLOR: SEE TABLE BODY: BRASS (ASTM B-19) .032 THK FINISH: SEE TABLE
DESCRIPTION	PART NO.	MATERIAL & FINISH

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN JR RUTH 06OCT00	TE Connectivity			
DIMENSIONS: INCHES		CHK T MICHIELUTTI 06OCT00				
		APVD T MICHIELUTTI 06OCT00	NAME			
		PRODUCT SPEC	SPLICE, RECEPTACLE, FASTON, .250 SERIES WIRE SIZE: 22-10			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .008 4 PLC ± - ANGLES ± - FINISH		—	A2	00779	C=321235	—
MATERIAL SEE TABLE		WEIGHT —	CUSTOMER DRAWING		SCALE NTS	SHEET 1 of 1
					REV U6	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[8-321235-1](#) [1-321235-4](#)