CATALOG LISTING **V3L-3** MICRO SWITCH SWITCH-BASIC CQ-A0300 FED. MFR. CODE 91929 CORROSION RESISTANT STEEL ACTUATOR 4-40 NC X .125 REF ROUND HEAD TERMINAL SCREW AND LOCKWASHER (3) : 19 DIA X.19 WIDE OIL BRONZE ROLLER (CONCENTRICITY . 005 TIR) .8ŀ .060 MAX 114 + .002 DIA HOLE **PRETRAVEL** .32 -10 .810±.030 OPERATING POSITION .406±.003 .25 .625± .015 .76 COM REVISIONS .114 + 002 A 16973 G C H .126 ± .002 DIA B CO 20189 M B F 7 SEP 65 126 C C021900 $.875 \pm .003$:27 D CO 24941 -1.094±.015----27 E C0 26075 7 AUG 69 CO 31509 THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH. DCS JAN94 CHARACTERISTICS **ELECTRICAL DATA** SCALE FULL CONTACT ARRANGEMENT OPERATING FORCE - - - - 14 OZ MAX DO NOT SCALE PRINT SPDT UNLESS OTHERWISE FEB RELEASE FORCE - -- - 3 OZ MIN SPECIFIED 15.1A 1/2HP 125 OR 250 VAC 1/2A 125 VDC, 1/4A 250 VDC 5A 125 VAC "L" DIMENSIONS ARE IN INCHES TOLERANCES ARE: 4 DIFFERENTIAL TRAVEL ---- OIG MAX ONE PLACE TWO PLACE THREE PLACE ANGLES ±.030 ±.015 ±.008 ± (.0) (.00) OVERTRAVEL - - - - - - .040 MIN ۵ RELEASE TRAVEL- ---- .007 MIN **B** *LR* WEIGHT

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

 $\frac{\text{Honeywell}}{\frac{\text{V3L-3}}{}}$