

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.


|                                                |                                                                                                                                                |
|------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Material                                       | High Conductivity Seamless Copper Tube                                                                                                         |
| Plating                                        | Electro-Tin                                                                                                                                    |
| Wire Size                                      | 2/0 AWG                                                                                                                                        |
| Wire Type                                      | Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric                                                               |
| Wire Strip Length                              | 3/4 in.                                                                                                                                        |
| Stud Size                                      | 3/8 in.                                                                                                                                        |
| UL Listed Wire Connector                       | Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts. |
| UL Temperature Rating                          | 90° C                                                                                                                                          |
| C.S.A Certified Wire Connector                 | Yes                                                                                                                                            |
| Panduit Color Code on Barrel                   | BLACK                                                                                                                                          |
| Panduit Die Index No. on Barrel                | P45                                                                                                                                            |
| Alternate Industry Die Index No. ( ) on Barrel | (13)                                                                                                                                           |



CERTIFIED



LISTED  
Wire Connector



|     |      |     |     |             |       |
|-----|------|-----|-----|-------------|-------|
| 00  | 8/02 | SAB | DRL | RELEASED    | 10325 |
| REV | DATE | BY  | CHK | DESCRIPTION | ECN   |

**PANDUIT**

**CORP. TINLEY PARK, ILLINOIS**

LCAS2/0-38H-X  
Copper Lug - One-Hole, Short Barrel, 45° Angle Tongue

SCALE  
N/A

DRAWING NO / CAD FILE

LCAS2\_0-38H-CUST

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[LCAS2/0-38H-X](#)