



SPECIFICATIONS		INPUT		OUTPUT		CONSTANT CURRENT LOAD
WIRING	VOLTS	HERTZ	VOLTS	MAX. AMPS	MAX. KVA	
SINGLE PHASE	120	50/60	0-140	4	0.56	

UNLESS OTHERWISE SPECIFIED, TOLERANCE IS ±
 DECIMALS .000 .005 .000 .01 .01 1° 1-1/2°
 HOLES ANGLES DRAFT UNITS IN [mm]
 XXXX XXXX XXXX XXXX XXXX XXXX XXXX XXXX

MATERIAL: ALL DIMENSIONS APPLY AFTER PLATING

The information and design disclosed herein was originated by and is the property of STACO ENERGY PRODUCTS CO., which reserves all patent, proprietary, design, manufacturing, reproduction, use and sole rights thereto, and to any article disclosed therein, except to the extent rights are expressly granted to others. The foregoing does not apply to vendor proprietary parts.

TITLE: SPEC. CONTROL DRAWING
VARIABLE TRANSFORMER
MODEL: 3PNJ401B
DRAWN BY: S.A. SMITH DATE: 6/4/96 FIRST USED ON: 3PNJ401B DO NOT SCALE DWG.
CHECKER: DATE: WEIGHT APPROX.: 21 LBS CODE IDENT. NO.: 83008
ENGINEER: DATE: SCALE: 1=1 SHEET 1 OF 1
CUSTOMER APPROVAL DATE
DWG. SIZE D DWG. NO. 031-8875

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Staco:](#)

[3PNJ401B](#)