

REV. 0  
DCO 142167

COIL: @ 25°C	
RESISTANCE	390 OHMS ± 10%
NOMINAL VOLTAGE	12.0 VDC
MUST OPERATE	7.0 VDC
	0.27 mADC
MUST RELEASE	4.0 VDC MAX, 0.63 VDC MIN.


ENVIRONMENT:	
VIBRATION	10 CPS TO 3000 CPS @ 30 g's
SHOCK	75 g's 6 MS. DURATION
TEMPERATURE	-65 °C TO +125 °C

NOTES:	
	TURN-ON TIME 2.0 MS MAX
	TURN-OFF TIME 7.5 MS MAX
	CONTACT STABILIZATION TIME 2.0 MS MAX

CUST. QPL  
CUST. NO. M28776/1-016P REV. \_\_\_\_\_

JMAT RELAY

CUSTOMER DATA SHEET



CONTACT RATING: LOW LEVEL TO 1A  
28 VDC RESISTIVE 100,000 OPERATIONS

DR. R.B. 4/16/98

*CK* *ERR* *7/6/00*

**COMMUNICATIONS**  
**INSTRUMENTS, INC.**

JMAWT-12XP

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[JMAWT-12XP](#)