

Plastic label with drill hole - EMLP 32 (38X14) SR - 0822343

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Plastic label with drill hole, Card, silver, unlabeled, can be labeled with: Engraving, Plotter, Mounting type: Adhesive, Lettering field: 38 x 14 mm



Product Features

- Can be engraved using the P1 ENGRAVING UNIT
- Can be labeled easily using the CMS-P1-PLOTTER
- Labeling service: Phoenix Contact can custom-label all EMLP ... markers according to your requirements
- High-quality appearance
- High level of resistance to chemical and mechanical influences
- For marking components, devices, and buttons



Key Commercial Data

| | |
|--------------------------------------|----------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 23.7 g |
| Custom tariff number | 39203000 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|------------|-------|
| Length (b) | 50 mm |
| Width (a) | 38 mm |

Ambient conditions

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 120 °C |
|---------------------------------|-------------------|

General

| | |
|------------|--------------------------------|
| Color | silver |
| Components | free from silicone and halogen |
| Material | TRANSPLY-ABS |

Plastic label with drill hole - EMLP 32 (38X14) SR - 0822343

Technical data

General

| | |
|--|----------------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels | 6 |
| Number of individual labels per row | 2 |
| RoHS compliant | Yes |
| Adhesive | Acrylic |
| Printability | Thermal transfer |
| Device | 5146257 THERMOMARK S1.1 |
| | 5146231 THERMOMARK X1.2 |
| | 5146477 THERMOMARK ROLL |
| | 5145313 THERMOMARK S1 |
| | 5145274 THERMOMARK X1.1 |
| Ink ribbon | 5145384 THERMOMARK-RIBBON 110 |
| | 0829544 THERMOMARK-RIBBON 110 BU |
| | 0829542 THERMOMARK-RIBBON 110 GN |
| | 0829543 THERMOMARK-RIBBON 110 RD |
| Test specification weathering-resistance | Following ISO 4892-2:2013-03 |
| Test duration | 96 h |
| Wipe resistance test result | Test passed |
| Salt spray test specification | DIN EN ISO 9227:2012-09 |
| Test duration | 96 h |
| Salt spray testing result | Test passed |
| Alternating condensation climate with SO2 test specification | DIN 50018:2013-05 |
| Climate level | AHT 1.0 S |
| Cycles | 2 |
| Condensation test result | Test passed |
| Wipe resistance of test specification inscriptions | IEC 61010-1:2010-06 |
| Result | Test passed |
| Burning behaviour | self-extinguishing |
| Foil strength | 175 µm |
| Adhesive strength | 400 µm |
| Marking mounting type | Adhesive |

Standards and Regulations

| | |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

Plastic label with drill hole - EMLP 32 (38X14) SR - 0822343

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 24190208 |
| eCl@ss 4.1 | 24190208 |
| eCl@ss 5.0 | 27149103 |
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27141137 |
| eCl@ss 7.0 | 27141137 |
| eCl@ss 8.0 | 27149129 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC001288 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121410 |

Accessories

Accessories

Magazine

Magazine - CMS-P1-M/GPE ENGRAVING - 5145711



Magazine for CMS-P1-PLOTTER, to accommodate GPE materials, especially for the purpose of engraving

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[0822343](#)