



CLAMPING SCREW

0.5

INTERLOCKING FEATURE

12.5

WIRE ENTRY

2.5 REF

1.00±0.01 TYP

5.00±0.05 TYP

5.0

15.0

35°

0.80±0.05 TYP

6.25 TYP

3.80±0.30 TYP

Ø 1.4<sup>+0.1</sup><sub>-0</sub>

Ø 0.1

MATERIALS AND FINISH:

HOUSING: PA 6-6, UL 94-V0, COLOR: BLACK.

CLAMP: BRASS, NICKEL PLATED.

TERMINAL: BRASS, TIN PLATED.

CLAMPING SCREW: M3, BRASS, NICKEL PLATED.

SUITABLE FOR 1,6-2,4mm PCB THICKNESS.

END-TO-END STACKABLE W/INTERLOCK, WITHOUT LOSS OF CENTERLINE SPACING.

WIRE RANGE: 12-30 AWG.

RECOGNIZED UNDER THE COMPONENT PROGRAM OF UNDERWRITERS LABORATORIES INC. FILE N° E60677.

IMQ CERTIFICATE WITH SURVEILLANCE IN CONFORMITY WITH IEC 998-1/998-2-1.

NOT CUMULATIVE TOLERANCE.

120.0	24	2-796689-4
115.0	23	2-796689-3
110.0	22	2-796689-2
105.0	21	2-796689-1
100.0	20	2-796689-0
95.0	19	1-796689-9
90.0	18	1-796689-8
85.0	17	1-796689-7
80.0	16	1-796689-6
75.0	15	1-796689-5
70.0	14	1-796689-4
65.0	13	1-796689-3
60.0	12	1-796689-2
55.0	11	1-796689-1
50.0	10	1-796689-0
45.0	9	796689-9
40.0	8	796689-8
35.0	7	796689-7
30.0	6	796689-6
25.0	5	796689-5
20.0	4	796689-4
15.0	3	796689-3
10.0	2	796689-2
L	NO OF POSN	PART NUMBER

DWN

S. WELDON

02SEP2003

CHK

C. RICHARD

02SEP2003

APVD

C. RICHARD

02SEP2003

PRODUCT SPEC

108-20166

APPLICATION SPEC

114-20079

WEIGHT

-

CUSTOMER DRAWING

SCALE 3.1

SHEET 1

OF 1

REV A1

TE Connectivity

NAME

TERMINAL BLOCK, PCB MOUNT

ANGLED WIRE ENTRY, STACKING

W/INTERLOCK, 5.00mm PITCH

SIZE

A2

CAGE CODE

00779

DRAWING NO

796689

RESTRICTED TO

-

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[796689-6](#)