

1 ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS

TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD

 $\overline{3}$ the noted dimensions apply at the intersection of the post and housing

AD 00

YOUNT OF MEASUREMENT FOR PLATING THICKNESS

OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

| | | 3.984 | 3.900 | 39 | 80 | 4-102973-0 | |
|-------------|----------------------|---------|-------|-------------|------------------|----------------|--------|
| | <u>S</u> OBSOLETE | 3.884 | 3.800 | 38 | 78 | 3-102973-9 | |
| | | 3.784 | 3.700 | 37 | 76 | 3-102973-8 | |
| | | 3.684 | 3.600 | 36 | 74 | 3-102973-7 | |
| | | 3.584 | 3.500 | 35 | 72 | 3-102973-6 | |
| | ODSOLLIL | 3.484 | 3.400 | 34 | 70 | 3-102973-5 | |
| | | 3.384 | 3.300 | 33 | 68 | 3-102973-4 | |
| | | 3.284 | 3.200 | 32 | 66 | 3-102973-3 | |
| | | 3.184 | 3.100 | 31 | 64 | 3-102973-2 | |
| <u>/</u> 5\ | OBSOLETE | 3.084 | 3.000 | 30 | 62 | 3-102973-1 | |
| | V | 2.984 | 2.900 | 29 | 60 | 3-102973-0 | |
| | OBSOLETE | 2.884 | 2.800 | 28 | 58 | 2-102973-9 | |
| | | 2.784 | 2.700 | 27 | 56 | 2-102973-8 | |
| | | 2.684 | 2.600 | 26 | 54 | 2-102973-7 | |
| | | 2.584 | 2.500 | 25 | 52 | 2-102973-6 | |
| | | 2.484 | 2.400 | 24 | 50 | 2-102973-5 | |
| | | 2.384 | 2.300 | 23 | 48 | 2-102973-4 | |
| | <u>\$</u> | 2.284 | 2.200 | 22 | 46 | 2-102973-3 | 1 |
| | OBSOLETE | 2.184 | 2.100 | 21 | 44 | 2-102973-2 | |
| | | 2.084 | 2.000 | 20 | 42 | 2-102973-1 | |
| | | 1.984 | 1.900 | 19 | 40 | 2-102973-0 | |
| | OBSOLETE | 1.884 | 1.800 | 18 | 38 | 1-102973-9 | - |
| /5 | OBSOLETE | 1.784 | 1.700 | 17 | 36 | 1-102973-8 | |
| | V | 1.684 | 1.600 | 16 | 34 | 1-102973-7 | |
| /5 | OBSOLETE | 1.584 | 1.500 | 15 | 32 | 1-102973-6 | |
| | | 1.484 | 1.400 | 14 | 30 | 1-102973-5 | |
| /5 | OBSOLETE | 1.384 | 1.300 | 13 | 28 | 1-102973-4 | |
| | • | 1.284 | 1.200 | 12 | 26 | 1-102973-3 | |
| | | 1.184 | 1.100 | 1 1 | 24 | 1-102973-2 | |
| | | 1.084 | 1.000 | 10 | 22 | 1-102973-1 | |
| | | .984 | .900 | 9 | 20 | 1-102973-0 | |
| | | .884 | .800 | 8 | 18 | 102973-9 | |
| | | .784 | .700 | 7 | 16 | 102973-8 | |
| | | .684 | .600 | 6 | 14 | 102973-7 | |
| | | .584 | .500 | 5 | 12 | 102973-6 | |
| | | .484 | .400 | 4 | 10 | 102973-5 | |
| | | .384 | .300 | 3 | 8 | 102973-4 | |
| | | .284 | .200 | 2 | 6 | 102973-3 | |
| | | .184 | .100 | 1 | 4 | 102973-2 | |
| | | .084 | | | 2 | 102973-1 | |
| | | C | В | \triangle | NO OF POSN | PART NUMBER | · · |
| DWN | | 150CT87 | | | | | |

REVISIONS

DESCRIPTION

23APR2014 NK MM

G REVISED PER ECO-14-000068

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 4-102973-0