

AT Serial Modem Gold Cable (DB25 to DB9 M/F), 6-ft

MODEL NUMBER: **P404-006**



Description

6ft serial modem cable. DB25M to DB9F. Superior molded cables with built-in strain relief ensures the cable will last a very long time. Foil-shielding provide maximum EMI/RFI protection. Gold plated connectors and gold plated copper contacts offer superior conductivity.

Features

- Superior molded cables with built-in strain relief ensures cable will last a very long time
- Foil-shielding provide maximum EMI/RFI protection
- Gold plated connectors and gold plated copper contacts offer superior conductivity

Specifications

INPUT	
Cable Length (ft.)	6
Cable Length (m)	1.8
PHYSICAL	
Color	Black
CONNECTIONS	
Side A - Connector 1	DB9 (FEMALE)
Side B - Connector 1	DB25 (MALE)
CERTIFICATIONS	
Certifications	RoHS-Compliant

Highlights

- Superior molded cables with foil-shielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity
- Use to connect your computers serial port to an external modem

System Requirements

- Hayes compatible external modem with a Female DB25 port.
- Computer with an available DB9 Male serial port

Package Includes

- 6Ft Serial Modem Cable DB9F/25M



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Tripp Lite:](#)

[P404-006](#)