

A




SIX (6)
RECEPTACLES
20 AMP, 250V
TWIST LOCK
NEMA L6-20R

MODEL FILENAME		09V098CC/01.PRT	
CAD FILENAME/LAYERS		09V098CC_DC/01A.PRT	
PANDUIT CORP TINLEY PARK, ILLINOIS			
2RU HORIZONTAL, (6) L6-20R, METERED POWER OUTLET UNIT CUSTOMER DRAWING			
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: INCHES X.X +/- 0.03 X.XX +/- 0.015 X.XXX +/- 0.005		UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION	
[METRIC - MILLIMETER] X. +/- 0.8 X.X +/- 0.4 X.XX +/- 0.13		ANGLE +/- 1°	
DRAWN BY MAV	MAT'L:	SCALE NONE	
DATE 2-24-11		DRAWING NO. 09V098CC	DWG B
CHK'D KRKE			

9. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE, AND LOCAL CODES.

PANDUIT P/N	WEIGHT
HB1B1E0BA06J1	14 lb (6.3 kg)



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[HB1B1E0BA06J1](#)